

2025 CATALOG

COMMERCIAL LANDSCAPE EQUIPMENT

60V^{MAX} BATTERY / REVOLUTION® ELECTRIC / GAS POWERED



TORO®

ZERO-TURN MOWERS | STAND-ON MOWERS | WALK-BEHIND MOWERS
TURF RENOVATION | SNOW REMOVAL | PROFESSIONAL HANDHELD
PARTS & ACCESSORIES

Count on it.

*Battery manufacturer rating = 60V maximum & 54V typical usage. Actual voltage varies with load.

FROM START TO FINISH

THE FUTURE OF LAWN CARE AND YOUR BUSINESS IS HERE. EXPERIENCE A REVOLUTION IN LAWN CARE.

There's a revolution, born from 100 years of perfecting lawn care. Powered by the Toro-developed HyperCell® battery system, these machines provide all-day runtime. Because they're built on proven platforms, utilizing TURBO FORCE® decks, expect the trusted quality and performance Toro consistently delivers. Experience a revolution in the way professionals care for lawns.



BIG TIME POWER

The same big-block power you expect from gas, but with constant power delivery.



HORIZON360 INTEGRATION

Basic Horizon360 functionality is standard on Revolution models, and allows you to check machine battery data and status.



OUTLAST THE DAYLIGHT

HyperCell batteries communicate with each other to place a priority on efficiency and extended life, giving you power to get the job done.



ALL DAY, EVERY DAY RELIABILITY

No more valve adjustments, oil changes, and air filter management. Say hello to HyperCell reliability and big-time longevity.



HORIZON360
CONTRACTOR BUSINESS SOFTWARE

COMPATIBLE

	GRANDSTAND® STAND-ON MOWERS						Z MASTER® ZERO TURN MOWERS										
											REAR DISCHARGE		MyRIDE® SUSPENSION				
	18562		18560		18564		18748		18752		18760		18762		18765		
POWER SYSTEM																	
Battery	HyperCell						HyperCell										
Battery Quantity	8		8		8		10		10		10		10		10		
Battery Capacity	18.4 kWh		18.4 kWh		18.4 kWh		23.4 kWh		23.4 kWh		23.4 kWh		23.4 kWh		23.4 kWh		
Runtime (hrs)	4 - 7+		4 - 7+		4 - 7+		4.5 - 7+		4.5 - 7+		4.5 - 7+		4.5 - 7+		4.5 - 7+		
Charge Time (hrs)	12		12		12		8		8		8		8		8		
Charge Type	1.2 kW 120V						3.3 kW available summer 2024; Also compatible with 1.2 kW 120V Standard										
TRACTION																	
Transmission	Planetary Gearset						Planetary Gearset										
Motors	Commercial High Torque						Commercial High Torque										
MOWING DECKS																	
Deck Size	48" (122 cm)		► 52" (132 cm)		60" (152 cm) Rear Discharge		48" (122 cm)		► 52" (132 cm)		► 60" (152 cm)		► 60" (152 cm)		60" (152 cm)		
Cutting Deck	7-Gauge TURBO FORCE®						7-Gauge TURBO FORCE®										
Deck Depth	5.5" (14 cm)						5.5" (14 cm)										
Spindle Housings	9" (22.9 cm) Diameter Cast Aluminum w/ Blade Retainer						9" (22.9 cm) Diameter Cast Aluminum w/ Blade Retainer										
Cutting Height	1.5" - 5.0" in .25" increments (3.8 – 12.7 cm in .6 cm increments)						1.5" - 5.5" in .25" increments (3.8 – 14.0 cm in .6 cm increments)										
Blades	.204" (.5 cm) Heat-Treated Steel						.204" (.5 cm) Heat-Treated Steel										
Blade Tip Speed	Adjustable						Adjustable										
Electric Deck Lift	N/A						Optional										
Motors	Mid-Mount Commercial High Torque						Mid-Mount Commercial High Torque										
Rake Adjustment	Yes						Yes										
FEATURES																	
MyRIDE® Suspension System	N/A						N/A										► Standard
Operator Seat	N/A						Deluxe Suspension Comfort w/Armrests										
Max Traction Unit Speed (advertised)	10 mph (16.1 km/h)						11 mph (17.7 km/h)										
Max Traction Speed Control	Yes - 7 speed settings						Yes - 7 speed settings										
Drive Tires	Super Turf 20" x 10" x 10" (50.8 x 25.4 – 25.4 cm)						Super Turf 24" x 9.5" x 12" (61 x 24.1 – 30.5 cm)		► Super Turf 24" x 10.5" x 12" (61 x 26.7 – 30.5 cm)		► Super Turf 24" x 12" x 12" (61 x 30.5 – 30.5 cm)						
Drive Wheels	Black Steel						Black Steel										
Front Caster Tires	11" x 4" - 5" Flat-Free Semi-Pneumatic (27.9 x 10.2 – 12.7 cm)						13" x 6.5" - 6" Flat-Free Semi-Pneumatic (33 x 16.5 – 15.2 cm)										
Technology	Hour Meter, USB, Horizon 360 Included						Hour Meter, USB, Horizon 360 Included										
ROPS Profile / PIN Type	N/A						Square Tube / Pin w/Lanyard										
Knee Pad	Deluxe Durable						N/A										
Operator Platform	Foldable w/Bumper Cushions						N/A										
LED Lights	Standard						Standard										
Parking Brake	Integrated in Transmission - Automatic						Integrated in Transmission - Automatic										
Horizon360 Capability	Yes						Yes										
Mower Warranty*	5-Year 1200-Hour; 2-Year No Hour Limit						5-Year 1250-Hour; 2-Year No Hour Limit										
WEIGHTS AND MEASUREMENTS																	
Weight	1,109 lbs.	503.0 kg	1,118 lbs.	507.0 kg	1,156 lbs.	525.0 kg	1,354 lbs.	614.2 kg	1,367 lbs.	620.1 kg	1,381 lbs.	626.4 kg	1,381 lbs.	626.4 kg	1,461 lbs.	662.7 kg	
ROPS Height (Folded)	N/A	N/A	N/A	N/A	N/A	N/A	46.3"	117.6 cm	46.3"	117.6 cm	46.7"	118.6 cm	118.6 cm	118.6 cm	49.9"	126.7 cm	
ROPS Height (Upright)	N/A	N/A	N/A	N/A	N/A	N/A	71.6"	181.9 cm	71.6"	181.9 cm	72.1"	183.1 cm	183.1 cm	183.1 cm	72.1"	183.1 cm	
Deck Clearance Width	49.6"	126.0 cm	53.8"	136.7 cm	61.8"	157.0 cm	52.2"	132.6 cm	55.6"	141.2 cm	60.4"	153.4 cm	153.4 cm	153.4 cm	60.4"	153.4 cm	
Deflector Width	63.6"	161.5 cm	67.8"	172.2 cm	75.8"	192.5 cm	63.1"	160.3 cm	67.2"	170.7 cm	75.2"	191.0 cm	191.0 cm	191.0 cm	75.2"	191.0 cm	
Length (Platform Up)	61.0"	154.9 cm	61.0"	154.9 cm	64.8"	164.6 cm	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
Length	75.8"	192.5 cm	75.8"	192.5 cm	78.9"	200.4 cm	81.6"	207.3 cm	81.6"	207.3 cm	81.6"	207.3 cm	81.6"	207.3 cm	81.6"	207.3 cm	

*Warranty does not include battery. See your local Toro dealer or consult owners manual for complete warranty details.

► = Step Up Feature

60V MAX* BATTERY

PROFESSIONAL HANDHELD PRODUCTS



REVOLUTION®



POWER FOR EVERY PROFESSIONAL

Revolution professional handheld products run on our 60V MAX* Flex-Force Power System* and work with our entire line of 60V Max* batteries. The backpack, available as a power source for our leaf blower, string, and hedge trimmers, is built for comfort and ready to keep jobs moving all day. It has the capacity for you to swap batteries, so when one battery is done, you're not. Our 60V Max* power comes to you fast: just 40 minutes to charge our largest battery to 100% and easily outpacing the charging speed of larger, lower voltage batteries.



REVOLUTION BACKPACK

Model 66000T

- Powered by any 60V Max* Flex-Force Battery
- Removable battery system with capacity for up to two batteries
- Interchangeable arm cannon or power tether
- Comfortable and sturdy backpack system for all day operation
- Integrated carrying handle
- Onboard LED battery diagnostics
- Tool only, batteries and chargers sold separately



60V MAX* 10 AH BATTERY

Model 66810

- The highest capacity 60V Flex-Force battery
- Increased max charging speed thanks to 4P pack design
- Easily removable and can be quickly swapped to refuel tools
- Integrated carrying handle
- Increased over-mold for ruggedization and drop resistance
- Weighs 8.2 lbs.



60V MAX* 6-POD CHARGER

Model 66550

- 12 AMP rapid charger
- 6 pod capacity
- Can charge any combination of 60V Flex-Force batteries
- 2 charge modes
- Sequential rapid mode can charge a single 10 Ah battery in 40 minutes
- Standard equal mode slowly brings all batteries up to full charge collectively



REVOLUTION POWERLINK TETHER

Model 66005

- Removes battery weight from tool to lessen operator fatigue
- Doubles handheld tool battery capacity
- Keeps your backpack power source connected to your handheld tools



REVOLUTION BACKPACK LEAF BLOWER

Model 66100

- Comfortable, sturdy backpack with integrated handle, LED battery diagnostics and two battery capacity
- Interchangeable arm cannon or power tether
- Powerful blower, 730 CFM at 160 MPH
- Variable speed trigger with turbo boost and cruise control
- Included storage strap for compact footprint
- Tool only, batteries and chargers sold separately

	REVOLUTION BLOWER CANNON (BARE TOOL)
Boost Mode	37 min
High Run Time [§]	80 min
Peak Run Time [§]	330 min
Weight (Bare Tool)	17.4 lbs.
CFM	730 CFM
MPH	160 MPH



REVOLUTION STRING TRIMMER

Model 66110T

- Rugged solid shaft design
- 16" cutting width with .095" line
- Bump-feed/easy-load head with increased line capacity and durability
- Rear mounted high efficiency brushless motor
- Variable 2-speed operation
- Tool only, batteries and chargers sold separately

	REVOLUTION STRING TRIMMER (BARE TOOL)
High Run Time [§]	160 min
Peak Run Time [§]	240 min
Weight (Bare Tool)	10.1 lbs.
RPM	6400/5300



REVOLUTION HEDGE TRIMMER

Model 66120T

- 26" bar with 1.2" cut capacity
- Dual-sided cutting blades
- 180° rotating handle for vertical or horizontal cutting
- Top side blade guard for operator protection and plant gathering
- Variable 2-speed with 3200/4100 spm
- Blade reverse mode for unsticking jams
- Class-leading run time*: up to 600 minutes
- Tool only, batteries and chargers sold separately

	REVOLUTION HEDGE TRIMMER (BARE TOOL)
Peak Run Time [§]	600 min
Weight (Bare Tool)	9.2 lbs.
Strokes per Minute	4100/3200

60V^{MAX} BATTERY LINEUP

	60V MAX* BATTERY (2.0AH)	60V MAX* BATTERY (2.5AH)	60V MAX* BATTERY (4.0AH)	60V MAX* BATTERY (5.0AH)	60V MAX* BATTERY (6.0AH)	60V MAX* BATTERY (7.5AH)	60V MAX* BATTERY (8.0AH)	60V MAX* BATTERY (10.0AH)
MODEL	88620	88625	88640	88650	88660	88675	88980	66810
CAPACITY (AMP-HOURS)	2.0 Ah	2.5 Ah	4.0 Ah	5.0 Ah	6.0 Ah	7.5 Ah	8.0 Ah	10.0 Ah
CAPACITY (WATT-HOURS)	108 Wh	135 Wh	216 Wh	270 Wh	324 Wh	405 Wh	432 Wh	540 Wh
PACK DESIGN	1P	1P	2P	2P	3P	3P	4P	4P
WEIGHT	3.7 lbs / 1.7 kg	3.7 lbs / 1.7 kg	5.2 lbs / 2.3 kg	5.5 lbs / 2.5 kg	6.9 lbs / 3.1 kg	7 lbs / 3.2 kg	7.9 lbs / 3.6 kg	8.2 lbs / 3.7 kg
CHARGE TIME*								
1 AMP CHARGER	110 minutes	130 minutes	220 minutes	260 minutes	330 minutes	395 minutes	440 minutes	535 minutes
2 AMP CHARGER	45 minutes	60 minutes	100 minutes	110 minutes	150 minutes	155 minutes	190 minutes	215 minutes
4 AMP 2-POD CHARGER	20 minutes	25 minutes	45 minutes	50 minutes	70 minutes	80 minutes	95 minutes	105 minutes
5.5 AMP RAPID CHARGER	20 minutes	25 minutes	35 minutes	40 minutes	50 minutes	60 minutes	70 minutes	75 minutes
12 AMP 6-POD CHARGER	20 minutes	25 minutes	30 minutes	35 minutes	45 minutes	50 minutes	35 minutes	40 minutes

*Battery manufacturer rating = 60V maximum & 54V typical usage. Actual voltage varies with load.
[§]Run time varies based on usage conditions. Max run time specs based on light conditions and/or lowest speed settings.

STAND-ON MOWERS

GRANDSTAND[®] MULTI FORCE[®]

MOST VERSATILE
STAND-ON ZERO TURN MOWER



WORKS YEAR-ROUND.



HORIZON360
CONTRACTOR BUSINESS SOFTWARE

COMPATIBLE

Switch attachments and boost profits no matter the season with the award-winning GrandStand MULTI FORCE stand-on mower. Snow or shine, this maneuverable machine combines the productivity of our proven, low-maintenance GrandStand mower with the ability to add attachments like the 5 ft. BOSS[®] plow for seasonal versatility.

ENJOY ALL-SEASON USE

With enhanced hydraulics and a patented movable front caster design. This allows optimal machine balance and power transfer for each attachment, whether you're clearing snow, blowing leaves or bagging debris.

INCREASE PRODUCTIVITY

With a new 10 mph max forward ground speed and an extra-large 10.5-gallon fuel tank.

SAVE MAINTENANCE AND TIME

With no hydraulic hoses, no daily/weekly grease points and a new engine design that allows extra room for service access.

EZ VAC POWERED BAGGER



The patent-pending side-mounted Soft Twin Bagger has a large 10 cu. ft. (8 bushel) (0.28 m³) capacity and the vertically-mounted blower allows for excellent maneuverability in tight spaces and maximum visibility.

EASILY REMOVABLE

Bagger frame conveniently removes with three pins and one bolt, while blower removes simply with one pin and a latch.

COMPACT

The side-mounted bagger offers a smaller width dimension.

SIDE-MOUNTED

Only stand-on machine with a side bagger to provide maximum visibility and excellent maneuverability.

BELT-DRIVEN

The blower/bagger system engages automatically with no additional engine required.

MODEL	DESCRIPTION
78524	GrandStand-Soft Twin Bagger Kit (use w/ 78525,78526,78527) [1]
78526	GrandStand E-Z Vac Blower & Drive Kit for 52" Deck
78527	GrandStand E-Z Vac Blower & Drive Kit for 60" Deck
107-1634	Bagger Enhancement Kit - 52" & 60"
132-4743	Hydro Filter Kit (contains 2 filters and O rings) (2016 and newer)
133-1437	Light Kit (48", 52" and 60" 2016 and newer)

	GRANDSTAND® MULTI FORCE®			
	72530		72524	
POWER SYSTEM				
Commercial Engines at 3600 RPM*	26.5 hp Kohler® Command PRO® EFI (747cc)		26.5 hp Kohler® Command PRO® EFI (747cc)	
Starter	Electric		Electric	
Heavy-Duty Canister Air Cleaner	Standard		Standard	
Drive Tires	20" x 10.5" – 8" (50.8 x 26.7 – 20.3 cm)		20" x 10.5" – 8" (50.8 x 26.7 – 20.3 cm)	
Caster Tires	11" x 4" – 5" Flat-Free Semi-Pneumatic (27.9 x 10.1 – 12.7 cm)		11" x 4" – 5" Flat-Free Semi-Pneumatic (27.9 x 10.1 – 12.7 cm)	
Fuel/Capacity	Gas/10.5-Gal (39.7 L)		Gas/10.5-Gal (39.7 L)	
Digital Hour Meter	Standard		Standard	
Hydraulic Drive System	Unitized Pumps & Wheel Motors (no hoses)		Unitized Pumps & Wheel Motors (no hoses)	
Pump	10cc/rev		10cc/rev	
Wheel Motor	10 cir		10 cir	
Maximum Forward Speed	10 mph (16.1 km/h)		10 mph (16.1 km/h)	
Clutch	Electromagnetic		Electromagnetic	
MOWING DECKS				
Deck Size	52" (132.1 cm)		► 60" (152.4 cm)	
Cutting Deck	7-Gauge TURBO FORCE®		7-Gauge TURBO FORCE®	
Bullnose Bumper	Standard		Standard	
Adjustable Discharge Baffle	Standard		Standard	
Rubber Discharge Chute	Standard		Standard	
Deck Lift Design	Extension Spring		Extension Spring	
Spindle Housings	9 3/8" (23.8 cm) Diameter Cast Aluminum		9 3/8" (23.8 cm) Diameter Cast Aluminum	
1" (2.5 cm) Heavy-Duty Spindle Shaft	Standard		Standard	
Spindle Bearings	Maintenance-Free		Maintenance-Free	
Cutting Height	1.5" – 5.0" (3.8 – 12.7 cm)		1.5" – 5.0" (3.8 – 12.7 cm)	
Blades	.204" (.5 cm) Heat-Treated Steel		.204" (.5 cm) Heat-Treated Steel	
Blade Tip Speed	18,500+ ft/min		18,500+ ft/min	
Belt Construction	Aramid Fiber V-Belt		Aramid Fiber V-Belt	
Anti-Scalp Rollers	N/A		► Standard	
Carrier Frame Construction	3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)		3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)	
FEATURES				
Steering Controls	Twin Lever		Twin Lever	
Operator Platform	Foldable Operator Platform with Suspension		Foldable Operator Platform with Suspension	
WEIGHTS AND MEASUREMENTS				
Weight	908 lbs.	411.9 kg	941 lbs.	426.8 kg
Height	48"	121.9 cm	48"	121.9 cm
Deck Width	54"	137.2 cm	62"	157.5 cm
Deflector Width	68"	172.7 cm	76"	193 cm
Length (Platform Up)	61"	154.9 cm	65"	165.1 cm
Length (Platform Down)	75"	190.5 cm	79"	200.7 cm

ACCESSORIES

MODEL	DESCRIPTION
137-4136	Caster Wheel Kit recommended for broom
133-1437	Light Kit (48", 52" and 60" 2016 and newer)
133-4603	Snow Tire (2016 and newer) (order 2 for a set)
133-5386	Wheel Weight Kit (MULTI FORCE 2016 and newer) recommended for broom
133-1437	Light Kit (48", 52" and 60" 2016 and newer)
133-1495	Strobe Flasher Light Kit (2016 and newer)
110-2025	Bagger Enhancement Kit - 40"
108-4091	Bagger Enhancement Kit - 48"
107-1634	Bagger Enhancement Kit - 52" & 60"
139-1529	Bagger Enhancement Kit
137-3920	Rubber Flap Kit - MULTI FORCE Broom
137-3952	Broom Bristle Refill Kit

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

► = Step Up Feature



VERSATILE ACCESSORIES

Enhance seasonal productivity with optional light kit, winter tires and flashers.



2" SQUARE RECEIVER

Standard with the MULTI FORCE is the Power Arm with 2" receiver, providing a quick attachment point where attachments can be connected to the unit.

ATTACHMENTS

GRANDSTAND® MULTI FORCE® STAND-ON MOWERS



MULCH FORCE

You have a job to do, and you want to get it done efficiently. Moving and spreading mulch is no easy task, especially when you use an old-fashioned wheelbarrow. Get with the times – the new Toro MULCH FORCE bucket helps you to move nearly twice as much mulch three times as fast per load as using a traditional wheelbarrow. The hydraulically driven MULCH FORCE dump enables you to easily dump the exact amount in tree rings or retainers. This is mulch efficiency at its finest.

MOVE BIG, MOVE FAST

Move up to 10.7 cubic feet and 250 lbs. of mulch at speeds up to 10 mph.

HIGHER LEVEL THINKING

Adjustable front door allows you to pull into mulch conveyors with 30" of ground clearance.

FINESSE AND PROTECT

Deposits mulch 10" away from front tires to eliminate tree ring damage.

MODEL	DESCRIPTION
78597	Mulch Force Bucket
140-4311	Pneumatic Castor Wheel Kit



TINE RAKE DETHATCHER



Turn your mower into the ultimate spring clean-up tool with MULTI FORCE front-mount tine rake dethatcher. Use the rake to remove thatch, embedded leaves and debris.

DOUBLE DUTY

Use throughout growing season to control thatch accumulation and reduce turf disease.

BORN TO PERFORM

Promote root development and make room for thicker turf, rake in seeds to accelerate germination, and clean up fall grass for a picture-perfect lawn.

QUICK-ATTACH SYSTEM

Easily attach with mount bar and two clevis pins.

MODEL	DESCRIPTION
78690	Tine Rake Dethatcher w/ Mount
78691	Tine Rake Dethatcher Mount Only
144-3842	2 transmission filter (includes; filters, O-Rings, Sealing Washer)
133-1437	Light Kit (48", 52" and 60" 2016 and newer)

HOOKER AERATOR



Puncture up to six holes per square foot with the 38" wide aerator. Tines pierce deep into the soil, hooking and lifting loose plugs of dirt that disperse quickly, spreading nutrients over the surface.

BORN TO PERFORM

Bring efficiency to a new level and aerate 66,000 square feet per hour at 5 mph.

COMMERCIAL CONVENIENCE

Obstacles are no match for this aerator with six floating rotor heads that lift independently, three caster assemblies with floating cast iron tine rotor heads, and swivel casters.

QUICK-ATTACH SYSTEM

Easily attach with mount bar and two clevis pins.

MODEL	DESCRIPTION
78694	38-IN Front Mount Hooker Aerator (order with 78695)
78695	Hooker Aerator Mount
MSC13950	Low Flow Hydraulics (BOSS)
137-4106	Lift Cylinder Lock Kit MULTI FORCE
133-1437	Light Kit (48", 52" and 60" 2016 and newer)

LEAF PLOW

Clear large areas quickly with the new MULTI FORCE Leaf Plow. At 55" wide, it moves a ton of leaves in a short time.

MOVES THE HEAVY, WET STUFF

The high-strength galvanized steel construction not only ensures long-term durability, it provides the strength to push heavy, wet leaves.

EASY ON SURFACES

The stainless-steel tines won't damage grass or turf.

EASY TRANSPORT

When your task is complete, the plow folds up over the deck, so it fits easily on your trailer.

MODEL	DESCRIPTION
78697	Leaf Plow w/o mount (order with 78698)
78698	Leaf Plow Mount
144-3842	Hydro Filter Kit (contains 2 filters and O rings) (2016 and newer)
133-1437	Light Kit (48", 52" and 60" 2016 and newer)

PRO FORCE® BLOWER



The Pro Force Blower has a 360° nozzle rotation and utilizes the MULTI FORCE 26.5 hp Kohler® Command Pro™ EFI engine to deliver tremendous air power for fast removal of grass clippings, leaves, or other debris.

EFFICIENT TURBINE-TYPE ASSEMBLY DESIGN

For greater air flow to move debris farther and finish the job faster. Rated at 7800 CFM.

DURABLE NOZZLE

Heavy-duty, single-piece rotomolded plastic nozzle resists impacts.

360° MOVEMENT

Nozzle and lower shield rotate 360° to give ultimate debris control. Easy directional control at your fingertips using the low flow controls and PTO switch.

MODEL	DESCRIPTION
78593	Pro Force Debris Blower (requires Low Flow)
MSC13950	Low Flow Hydraulics (BOSS)
137-4106	Lift Cylinder Lock Kit MULTI FORCE
133-1437	Light Kit (48", 52" and 60" 2016 and newer)

POWER BROOM



55" (139.7 cm) Power Broom is designed to tackle sidewalks and clear snow and debris down to the pavement.

FULLY HYDRAULIC POWER BROOM

Increase speed and efficiency with the high-performance hydraulic package.

QUICK-ATTACH SYSTEM

And three kickstands to easily swap Power Broom on and off.

225 REVOLUTIONS/MINUTE

To quickly clear snow, ice and debris.

MODEL	DESCRIPTION
78596	Power Broom (requires High and Low Flow)
78601	High Flow Hydraulics
136-0513	Quick Attach Kit- MULTI FORCE (2016 and newer) (req for MF attachments)
133-5386	WHEEL WEIGHT KIT (MULTI FORCE 2016 and newer)
137-3920	Rubber Flap Kit- MULTI FORCE Broom
140-4310	Snow Tire Kit (includes set)
140-4311	Pneumatic Castor wheel kit - MULTI FORCE (includes set)
136-8350	EC Float Kit Multiforce
133-1495	Strobe Flasher Light Kit (2016 and newer) Requires light kit
137-3952	Bristle Refill Kit- MULTI FORCE Broom
140-4290	Wheel and Bearing Assembly (11" Pneumatic)
144-3842	Filter kit (contains 2 filters, O-Rings and 4 sealing washers)
133-1437	Light Kit (48", 52" and 60" 2016 and newer)

BOSS® PLOW



Available in both 4' and 5', the BOSS plows are designed with productivity, durability, and operator safety in mind.

HIGH BLADE LIFT

With 30° lift height for superior snow-stacking.

FULL HYDRAULIC PLOW

Increase speed and efficiency with the low flow hydraulic package.

EXCEPTIONAL GROUND CLEARANCE

Will allow your unit to remain trail compatible.

CONTRACTOR-GRADE PLOW

Tough and rugged poly straight-blade*.

MODEL	DESCRIPTION	MODEL	DESCRIPTION
MSC14780	4' Plow Side Mount Kit (BOSS)	MSC13960	5' Plow Side Mount Kit (BOSS)
STB13759B	4' Snow Blade (BOSS) [requires low flow & 4' Plow Side Mount Kit]	STB13567B	5' Snow Blade (BOSS) [requires low flow & 5' Plow Side Mount Kit]
STB13802	4' URETHANE EDGE [5.0FTX 4X0.75, STB]	STB13801	5' URETHANE EDGE [5.0FTX 4X0.75, STB]

MODEL	DESCRIPTION
136-0513	Quick Attach Kit- MULTI FORCE (2016 and newer) (req for MF attachments)
133-5386	WHEEL WEIGHT KIT (MULTI FORCE 2016 and newer)
140-4310	Snow Tire Kit (includes set)
136-8350	EC Float Kit Multiforce
133-1495	Strobe Flasher Light Kit (2016 and newer) Requires light kit
133-1437	Light Kit (48", 52" and 60" 2016 and newer)
MSC04587B	Snow Deflector Kit
MSC13040	Plow Shoe Kit
MSC13870B	Box Wing Extension Set
MSC13850B	6" Blade Extension Kit
HDW13807	BOLT, CARRIAGE, 1/2"-13X2-1/2", GR5 BLKZ- used w/replacement Cutting Edge for Boss Plow on MULTI FORCE
144-3842	Filter kit (contains 2 filters, O-Rings and 4 sealing washers)
STB13803	Replacement Urethane Cutting Edge- Boss Plow used on MULTI FORCE



SNOW THROWER

Clear both tight and large spaces with the new MULTI FORCE Snow Thrower. At 48" wide, it is perfect for sidewalks but also big enough to make quick work of driveways and parking lots.

NO JARRING IMPACTS

Through a unique urethane trip edge that softens any contact with obstacles like uneven pavement, cobblestones, manhole covers and more.

HYDRAULIC CONTROL AND POWER

The lift and chute rotation are controlled by low-flow hydraulics for easy adjustments. The blower is powered by high-flow hydraulics to ensure there's plenty of power to throw piles of snow.

MODEL	DESCRIPTION
78598	48" Snow Thrower
78601	High Flow Hydraulics
133-5386	WHEEL WEIGHT KIT (MULTI FORCE 2016 and newer)
140-4311	Pneumatic Castor wheel kit (2 Tires)
140-4310	Snow Tire Kit (2 Tires)
136-8350	EC Float Kit Multiforce
133-1495	Strobe Flasher Light Kit (2016 and newer) Requires light kit
133-1437	Light Kit (48", 52" and 60" 2016 and newer)

PROLINE SERIES

MID-SIZE MOWERS



TIME SAVER. MONEY MAKER.



HORIZON360
CONTRACTOR BUSINESS SOFTWARE

COMPATIBLE

PROLINE SERIES						
44410		44424		44427		
44409 CARB		44423 CARB				
14.5 hp Kawasaki® FS	▶ 15 hp Kawasaki FS		▶ 18.5 hp Kawasaki FS			
Electric						
18"			▶ 20"			
9"			▶ 11"			
Gas / 5 Gal (18.9 L)						
Twin Lever						
ZT-2800						
Standard						
7 mph (11.3 km/h)						
Integrated Parking Brake						
36" (91.4 cm)		▶ 48" (121.9 cm)		▶ 54" (137.2 cm)		
10-Gauge Steel						
Standard						
-						
Standard						
8" Cast Aluminum						
Maintenance-Free						
1.5" – 4.5" (3.8 – 11.4 cm)						
.204" Heat-Treated Steel						
18,500+ ft./min.						
Aramid Fiber V-Belt						
Standard						
WEIGHTS AND MEASUREMENTS						
580 lbs.	263.1 kg	639 lbs	289.8 kg	648 lbs.	294.9 kg	
45"	114.3 cm	46"	116.8 cm	46"	116.8 cm	
37"	94.0 cm	49"	124.5 cm	55"	139.7 cm	
51"	129.5 cm	63"	160.0 cm	69"	175.3 cm	
77"	195.6 cm	80"	203.2 cm	80"	203.2 cm	

Contractors know every second not mowing is a lost opportunity, and training your crew on new equipment can cause unnecessary setbacks in time and money.

MAXIMIZE YOUR EFFICIENCY

With the Toro PROLINE mid-size mowers. Not only will your crew be mowing in no time with easy-to-learn controls, but you'll also enjoy top-line reliability and professional cutting performance.

YOU'LL LOVE THE CONVENIENCE

Of the 2-wheel sulky, which rotates 360° and simply folds away when not in use; no more attaching and removing when trailering! *Sold separately.*

AND YOU CAN REST EASY

Knowing that Toro stands behind its mowers with a 3-year, 750-hour warranty.

	PROLINE SERIES									
	44430		44436		44448		44454		44460	
POWER SYSTEM										
Commercial Engines at 3600 RPM*	▶ 22 hp Kawasaki FS		15 hp Kawasaki FX		▶ 22 hp Kawasaki FX					
Starter	Electric									
Drive Tires	▶ 20"		18"		▶ 20"					
Caster Tires	▶ 11"		9"		▶ 11"					
Fuel/Capacity	Gas / 5 Gal (18.9 L)									
Control System	Twin Lever									
Transmission	ZT-2800		▶ ZT-3100							
Hour Meter	Standard									
Maximum Forward Speed	7 mph (11.3 km/h)									
Brake System	Integrated Parking Brake									
MOWING DECKS										
Deck Size	▶ 60" (152.4 cm)		36" (91.4 cm)		▶ 48" (121.9 cm)		▶ 54" (137.2 cm)		▶ 60" (152.4 cm)	
Cutting Deck	10-Gauge Steel		7/10-Gauge Steel							
Bullnose Bumper	Standard									
Rubber Discharge Chute	-		▶ Standard							
Deck Lift Assist	Standard									
Spindle Housings	8" Cast Aluminum									
Spindle Bearings	Maintenance-Free									
Cutting Height	1.5" – 4.5" (3.8 – 11.4 cm)									
Blades	.204" Heat-Treated Steel									
Blade Tip Speed	18,500+ ft./min.									
Belt Construction	Aramid Fiber V-Belt									
Anti-Scalp Rollers	Standard									
WEIGHTS AND MEASUREMENTS										
Weight	693 lbs.	314.3 kg	608 lbs.	275.8 kg	669 lbs.	303.5 kg	695 lbs.	315.2 kg	730 lbs.	331.1 kg
Height	46"	116.8 cm	45"	114.3 cm	46"	116.8 cm	46"	116.8 cm	46"	116.8 cm
Deck Clearance Width	61"	154.9 cm	37"	94.0 cm	49"	124.5 cm	55"	139.7 cm	61"	154.9 cm
Deflector Width	75"	190.5 cm	51"	129.5 cm	63"	160.0 cm	69"	175.3 cm	75"	190.5 cm
Length	83"	210.8 cm	77"	195.6 cm	80"	203.2 cm	80"	203.2 cm	83"	210.8 cm

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

▶ = Step Up Feature



DRIVE WITH EASE

Shred grass in no time with the easy-to-learn twin-lever controls and drive assist with three settings.



MOWING MUSCLE

Ensure you never lose a job because of broken equipment with a reliable Kawasaki engine that drives .204" blades for a gorgeous, professional cut.



MADE TO LAST

Your Toro is also built to take on years of rough rides with a bullnose bumper and 20" wheels with curb clearance.



QUICK ADJUSTMENT

Changing cut lengths on the go is a snap with a single-point height of cut adjustment.



NO-HASSLE SULKY

The 2-wheel sulky simply folds away, meaning no need to attach and remove it when trailering.
(Part # 44401 Sold Separately)

TURBO FORCE®

CUTTING TECHNOLOGY

With more than 100 million hours of real world runtime and trillions of grass clippings under its belt, this cutting system has productivity and performance written all over it. The TURBO FORCE deck is designed to make the highest quality cut possible, while delivering you the power and productivity you need to efficiently knock out job after job, day after day. The perfect cut starts with a high-strength steel deck and cast aluminum spindle housings driving blade tip speeds up to 18,500 feet per minute. Deliver an extreme quality of cut at fast speeds, all day long, season after season, in all conditions.



HIGH-STRENGTH
CUTTING BLADES

BULLNOSE
FRONT BUMPER
DESIGN

FULLY-WELDED
FABRICATED
DECK SHELL

ADJUSTABLE
DISCHARGE
BAFFLE
Select Models

HEAVY-DUTY
GAUGE WHEELS

PATENTED RUBBER
DISCHARGE CHUTE

COMFORT ISN'T A LUXURY. IT'S A BUSINESS STRATEGY.

MyRIDE®

SUSPENSION SYSTEM

Mow fast and keep the operator operating. With an intuitive and easy-to-use suspension adjustment system, you can instantly lock into a comfort match that leaves you and your crew ready to take on more. Since your body doesn't take a pounding, you don't have to slow down. You'll get big jobs done faster than ever before. And by having the most comfortable mowers out there, happy crews are loyal crews. And loyal crews work harder and want to keep working with you.



PERSONALIZED RIDE SETTINGS

The operator can easily and quickly adjust rear shock ride settings to account for their personal ride preferences without the use of tools.



MAXIMUM COMFORT

The suspended operator platform allows up to 4" of travel (5000 series and up) and reduces impacts, bumps and vibrations that reach the operator, resulting in a superior ride.



HORIZON360®
CONTRACTOR BUSINESS SOFTWARE | A TORO® TECHNOLOGY



**SIGN UP
NOW!**

**HORIZON360 BUSINESS SOFTWARE ENABLES YOU TO
MORE EFFECTIVELY MANAGE EQUIPMENT, CREWS,
QUOTING AND BILLING.**

**LEAD YOUR BUSINESS EFFICIENTLY
FROM START TO FINISH.**

**SIGN UP AND
GET 10% OFF YOUR 1ST TORO PARTS ORDER!**
When ordered through the Horizon360 Parts Store.

**FLEET MEMBERS –
ENJOY UNLIMITED TIER + 2 GPS DEVICES FOR FREE!**
A \$2600 Value!

STREAMLINE OPERATIONS & BOOST PROFITABILITY.

**It's about easy-to-use solutions for your business, built by
contractors like you.**

Gain clarity into your operation like never before with Horizon360®. It's a contractor-grade software solution built to streamline and optimize every critical aspect of your business while reducing day-to-day chaos. Designed with better technology and a more intuitive user experience than other platforms, you'll be growing your operation—and your bottom line—in no time. Roll your to-do list into the industry's must-have software platform.

	Essential	Premium	Unlimited
No Obligation Free Trial	–	30 Days	60 Days
Customer Management	X	X	X
Scheduling & Dispatching	X	X	X
Employee Management	X	X	X
Equipment Management	X	X	X
Crew Mobile App	X	X	X
Invoice Management	X	X	X
Estimating		X	X
Routes		X	X
Analytics		X	X
Equipment Maintenance	X	X	X
Admin Mobile App	X	X	X
Tracking	+	+	X
Timecard Management	+	+	X
Route Optimization	+	+	X
CRM (Customer Communications)	+	+	X
Time & Materials	+	X	X
Monthly Fee	Free	\$99	\$199

SCHEDULING | TRACKING | INVOICES | ANALYTICS

HORIZON™
TECHNOLOGY

**ELITE
PERFORMANCE
IS ON THE
HORIZON.**

The next generation of HORIZON TECHNOLOGY is better than ever, with even more information at your fingertips on the expanded display. This onboard intelligence system is designed to enhance productivity and fuel efficiency with optimized performance in a wide range of mowing conditions.

LETS YOU CHOOSE THE PERFORMANCE MODE

To match the mowing conditions and reduce fuel consumption.

ALERTS YOU WHEN SERVICE IS NEEDED

Display tracks hours of operation until service is due and provides advanced machine health monitoring.

EXTENDS CLUTCH LIFE

By engaging and disengaging the clutch at optimal RPMs.

HORIZON TECHNOLOGY IS AVAILABLE ON SELECT Z MASTER® 6000 AND 7500 SERIES MODELS:

6000 72946 60" (152.4 cm) 38 hp Kohler® Command PRO® EFI
6000 72947 72" (182.9 cm) 38 hp Kohler Command PRO EFI
7500 72076 72" (182.9 cm) 37 hp Yanmar® Diesel
7500 72074 72" (182.9 cm) 37 hp Yanmar Diesel RD
7500 72098 96" (243.8 cm) 37 hp Yanmar Diesel RD
7500 72027 60" (152.4 cm) 25 hp Yanmar Diesel
7500 72028 60" (152.4 cm) 25 hp Yanmar Diesel RD
7500 72029 72" (182.9 cm) 25 hp Yanmar Diesel RD
7500 72030 72" (182.9 cm) 25 hp Yanmar Diesel
7500 74090 96" (243.8 cm) 38 hp Kohler Command PRO EFI
7500 72144 144" (365.7 cm) 44 hp Yanmar Diesel

See pages 21 and 23 for specifications.



ENHANCED CAPABILITIES

Horizon Technology now features a larger display screen with plain text error codes and added functionality. Operators can set defined maintenance reminders, monitor machine health and track machine hours by property.



DEFINED PERFORMANCE MODES

The engine speed is controlled by push-button controls to provide three defined performance modes:

LOW MODE

Helps reduce deck packing and discharge clumping in wet conditions.

ECONOMY MODE

Excellent performance in typical conditions with reduced fuel consumption, emissions, noise and wear.

MAX MODE

Maximum power for the most demanding conditions.

EFI MODELS

Z MASTER® AND GRANDSTAND® MOWERS
WITH ELECTRONIC FUEL INJECTION

If your fuel bills are on the rise, give them a cut with ELECTRONIC FUEL INJECTION (EFI) engines. They're designed to adapt to load, weather, fuel and altitude changes for faster response and overall better fuel economy.

GAIN FUEL EFFICIENCY

With significantly better fuel economy compared to comparable carbureted engines.

SAVE DOWNTIME

With flat-free, semi-pneumatic caster tires on select models.

BOOST PERFORMANCE

With high-capacity, commercial-grade hydrostatic drive systems.

Z MASTER® EFI MODELS:

2000 77288 60" (152.4 cm) 28 hp Vanguard EFI
4000 74035 60" (152.4 cm) 26.5 hp Kohler Command Pro EFI
All 5000 Models (Excluding 72910)
6000 72926 60" (152.4 cm) 26.5 hp Kohler Command PRO EFI
6000 72946 60" (152.4 cm) 38 hp Kohler Command PRO EFI
6000 72928 72" (182.9 cm) 26.5 hp Kohler Command PRO EFI
6000 72947 72" (182.9 cm) 38 hp Kohler Command PRO EFI
6000 72980 60" (152.4 cm) 37 hp Vanguard EFI
6000 72981 60" (152.4 cm) 37 hp Vanguard EFI
6000 72982 72" (182.9 cm) 37 hp Vanguard EFI
6000 72983 72" (182.9 cm) 37 hp Vanguard EFI
6000 72976 60" (152.4 cm) 38 hp Kohler CP EFI
6000 72977 72" (182.9 cm) 38 hp Kohler CP EFI
7500 74090 96" (243.8 cm) 38 hp Kohler Command PRO EFI

GRANDSTAND® EFI MODELS:

72518† 48" (121.9 cm) 23 hp Kohler Command PRO EFI
72519 52" (132.1 cm) 25 hp Kohler Command PRO EFI
72920 60" (152.4 cm) 28 hp Vanguard EFI
72513 60" (152.4 cm) 25 hp Kohler Command PRO EFI
72530 52" (132.1 cm) 26.5 hp Kohler Command PRO EFI
72524 60" MF (152.4 cm) 26.5 hp Kohler Command PRO EFI
72514 60" (152.4 cm) 37hp Vanguard EFI
72517 72" (182.9 cm) 37hp Vanguard EFI

† CARB compliant model

See pages 13, 15, 17, 19, 21, 23, 27 and 29 for specifications.

PRICE OF GASOLINE PER GALLON

\$3.00	\$3.25	\$3.50	\$3.75	\$4.00
--------	--------	--------	--------	--------

DOLLARS SAVED PER HOUR*

\$0.90	\$0.98	\$1.05	\$1.13	\$1.20
--------	--------	--------	--------	--------

DOLLARS SAVED IN FIRST YEAR*

\$540	\$585	\$630	\$675	\$720
-------	-------	-------	-------	-------

*Fuel savings dependent on ground mowing conditions when compared to carbureted engines. Kohler models only.

EXCELLENT LOAD RESPONSE

The EFI system delivers fuel where and when there is a demand, providing excellent load pickup and consistent power.

EFFORTLESS STARTING

EFI engines are easy to start in a range of altitudes and climates with no choke needed.

OUTSTANDING RELIABILITY

Sensors monitor the engine as it runs and lights warn you of potential issues. The investment quickly pays for itself with less service time.

INVEST IN YOUR FLEET, NOT FUEL.

Z MASTER®

2000 SERIES

SEE PAGE 2 FOR BATTERY
REVOLUTION SERIES OPTIONS



WORK FAST. WORK RIGHT.



HORIZON360
CONTRACTOR BUSINESS SOFTWARE

COMPATIBLE

The commercial-grade yet civilian-friendly Z Master 2000 gives you plenty of time and energy back with superbly capable, get-it-done-right productivity. Z Master 2000 is constructed to work and work and work, while not working you over. Using top-grade materials and engineering for both all-job toughness and all-rider ease, you will go fast, powerfully, comfortably, and be the master of your domain.

WORK FAST, WORK RIGHT

Step on it with speeds up to 10 MPH (miles per hour), and sacrifice nothing in quality. Power-packed engines deliver 25 HP* for clear-cut efficiency. Productivity rolls on traction-happy 24" rear tires. Our high-strength steel TURBO FORCE® cutting deck stands up to every challenge, pass after pass, day after day, year after year.

HIGHLY ENGINEERED BRUTE FORCE

This machine is built on a full tubular frame of 7-Gauge high-strength steel for rock-solid durability. Strong, tough cast aluminum forms our spindle housing for long-flying service. Our bullnose bumper is engineered with no-BS toughness.

SMOOTH OPERATOR

Our suspension seats are fully adjustable forward and backward, and customizable to your weight. Save your back and bones with MyRIDE® Suspension System (upgrade). Enjoy human-friendly seats with lumbar support, and perks like a USB port, cup holder and phone holder.

QUICK CARRY SYSTEM



TRIPLE THREAT UTILITY KIT

(145-3691) Attach tools and accessories directly to the mower with innovative tool-mounting brackets. Includes Bucket Holder Kit (147-63445), Universal Mount (147-6346) and Trimmer Mount (147-2665). *Sold separately.*




TURBO FORCE DECK

With heavy-duty cast aluminum spindle housings and the bullnose bumper, you get the master of all-conditions mowing muscle. Pro models available with flat-free semi-pneumatic caster tires.



CONFIDENTLY COMFORTABLE

Easily adjust the seat and ideal seat suspension to your preference. Customize your ride: Lights, Bucket Holder Kit (147-6345), Trimmer Mount (144-2662), Baggers, Mounts, and top 20 attachments.



MyRIDE® SUSPENSION SYSTEM

Take it to the next level of comfort with the industry's only adjust-on-the-fly rear suspension with beefy shocks featuring up to 3 inches of travel to soak up what Mother Nature puts in your path.

	HD						HDX MyRIDE® SUSPENSION SYSTEM				PRO	
	77281		77283		77285		77291 HDX		77294 HDX		77288	
POWER SYSTEM												
Commercial Engines at 3600 RPM*	Toro® 24.5 hp w/ HDAC						23.5 hp Kawasaki FX (726cc)				► 28 hp Briggs & Stratton® Vanguard EFI (810cc)	
Starter	Electric						Electric				Electric	
Heavy-Duty Donaldson® Canister-Style Air Cleaner	Standard						Standard				Standard	
Drive Tires	Voodoo Trac 24" x 9.5" – 12" (61 x 24.1 – 30.5 cm)	► Voodoo Trac 24" x 10.5" – 12" (61 x 26.7 – 30.5 cm)	► Voodoo Trac 24" x 12" – 12" (61 x 30.5 – 30.5 cm)	Voodoo Trac 24" x 10.5" – 12" (61 x 26.7 – 30.5 cm)		► Voodoo Trac 24" x 12" – 12" (61 x 30.5 – 30.5 cm)	Voodoo Trac 24" x 10.5" – 12" (61 x 26.7 – 30.5 cm)		► Voodoo Trac 24" x 12" – 12" (61 x 30.5 – 30.5 cm)	Voodoo Trac 24" x 12" – 12" (61 x 30.5 – 30.5 cm)		
Caster Tires	13" x 6.5" - 6" Pneumatic (33 x 16.5 – 15.2 cm)						13" x 6.5" - 6" Pneumatic (33 x 16.5 – 15.2 cm)				► 13" x 6.5" - 6" Flat-Free Semi-Pneumatic (33 x 16.5 – 15.2 cm)	
Fuel/Capacity	Gas/7-Gal (26.5 L)						Gas/7-Gal (26.5 L)				Gas/7-Gal (26.5 L)	
Digital Hour Meter	Standard						Standard				Standard	
Hydraulic Drive System	ZT-3400 Integrated Pumps & Wheel Motors						ZT-3400 Integrated Pumps & Wheel Motors				ZT-3400 Integrated Pumps & Wheel Motors	
Maximum Forward Speed	10 mph (16.1 km/h)						10 mph (16.1 km/h)				10 mph (16.1 km/h)	
Clutch	Electromagnetic						Electromagnetic				Electromagnetic	
MOWING DECKS												
Deck Size	48" (121.9 cm)	► 52" (132.1 cm)	► 60" (152.4 cm)	52" (132.1 cm)		► 60" (152.4 cm)	60" (152.4 cm)		60" (152.4 cm)			
Cutting Deck	7-Gauge TURBO FORCE™						7-Gauge TURBO FORCE™				7-Gauge TURBO FORCE™	
Bullnose Bumper	Standard						Standard				Standard	
Rubber Discharge Chute	Standard						Standard				Standard	
Deck Lift Design	Standard			► Lift Assist Spring			Standard		► Lift Assist Spring		Lift Assist Spring	
Spindle Housings	8" (20.3 cm) Dia. Aluminum						8" (20.3 cm) Dia. Aluminum				8" (20.3 cm) Dia. Aluminum	
1" (2.5 cm) Spindle Shaft	Standard						Standard				Standard	
Spindle Bearings	Maintenance-Free						Maintenance-Free				Maintenance-Free	
Adjustable Height of Cut Foot Pedal	Standard, 1.5" - 5" in .25" increments (3.8 – 12.7 cm in .6 cm increments)						Standard, 1.5" - 5" in .25" increments (3.8 – 12.7 cm in .6 cm increments)				Standard, 1.5" - 5" in .25" increments (3.8 – 12.7 cm in .6 cm increments)	
Deck Depth	5.5" (14.0 cm)						5.5" (14.0 cm)				5" (12.7 cm)	
Blades	.204" (.5 cm) Heat-Treated Steel						.204" (.5 cm) Heat-Treated Steel				.204" (.5 cm) Heat-Treated Steel	
Blade Tip Speed	18,500+ ft/min						18,500+ ft/min				18,500+ ft/min	
Belt Construction	Aramid Fiber V-Belt						Aramid Fiber V-Belt				Aramid Fiber V-Belt	
FEATURES												
MyRIDE® Suspension System							► MyRIDE Suspension System					
Comfort Platform	N/A	N/A	N/A								N/A	
Platform Travel	N/A	N/A	N/A				3.0" (7.6 cm)				N/A	
Shocks	N/A	N/A	N/A				1 center / 2 rear				N/A	
Seat	N/A	N/A	N/A				Deluxe Comfort				N/A	
Adjustability	N/A	N/A	N/A				5 Detents, Infinite Adjustability				N/A	
2" Hitch Receiver	Standard	Standard	Standard				Standard				Standard	
Steering Controls	1.4" (3.6 cm) Dia. Grips; Adjustable, Dampened						1.4" (3.6 cm) Dia. Grips; Adjustable, Dampened				1.4" (3.6 cm) Dia. Grips; Adjustable, Dampened	
Operator Seat	Deluxe Suspension						Deluxe Comfort				Deluxe Suspension	
Folding ROPS	Standard						Standard				Standard	
Tool-Mounting Capability	Side Console / Rear Guard Ready						Side Console / Rear Guard Ready				Side Console / Rear Guard Ready	
LED Lights	Standard						Standard				Optional	
USB Port	N/A						► Standard				N/A	
Step Through Floorpan	Standard						Standard				Standard	
Electric Deck Lift Assist	Optional						Optional				Optional	
Warranty**	4-Year 1000-Hour Limited						4-Year 1000-Hour Limited				4-Year 1000-Hour Limited	
WEIGHTS AND MEASUREMENTS												
Weight	870 lbs.	394.6 kg	890 lbs.	403.7 kg	920 lbs.	417.3 kg	1,012 lbs.	459 kg	1,036 lbs.	470 kg	920 lbs.	417.3 kg
ROPS Height (Folded)	49"	124.5 cm	49"	124.5 cm	49"	124.5 cm	49"	124.5 cm	49"	124.5 cm	49"	124.5 cm
ROPS Height (Upright)	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm
Deck Clearance Width	53"	134.6 cm	56.75"	144.1 cm	63.5"	161.3 cm	66"	167.6 cm	53"	134.6 cm	63.5"	161.3 cm
Deflector Width	63.25"	160.7 cm	67.25"	170.8 cm	75.25"	191.1 cm	75.25"	191.1 cm	63.25"	160.7 cm	75.25"	191.1 cm
Length	82"	208.3 cm	82"	208.3 cm	83"	210.8 cm	84.25"	214 cm	82"	208.3 cm	83"	210.8 cm

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower. **See your local Toro dealer or consult owners manual for complete warranty details.

► = Step Up Feature

Z MASTER®

4000 SERIES

SEE PAGE 2 FOR BATTERY
REVOLUTION SERIES OPTIONS



BUILT TO DOMINATE. READY TO REIGN.

Show up big, bad, and fearless. The Z Master 4000 is the durability king, providing a royal ride with MyRIDE® suspension system and grass-kicking TURBO FORCE® deck with a bold, dominating look. It's going to cut a path that you know will be noticed.



HORIZON360
CONTRACTOR BUSINESS SOFTWARE

COMPATIBLE

	HD		HDX MyRIDE® SUSPENSION SYSTEM					
	74050	74054	74052 HDX	74055 HDX	74057 HDX			
POWER SYSTEM								
Commercial Engines at 3600 RPM*	25.5 Kawasaki FX801V (852cc)		▶ 31 hp Kawasaki FX921V (999cc)		▶ 35 hp Kawasaki FX1000V (999cc)			
Starter	Electric		Electric					
Heavy-Duty Canister Air Cleaner	Standard		Standard					
Drive Tires	Voodoo Trac 26" x 10.5" - 12" (66 x 26.7 - 30.5 cm)	▶ Voodoo Trac 26" x 12" - 12" (66 x 30.5 - 30.5 cm)	Voodoo Trac 26" x 10.5" - 12" (66 x 26.7 - 30.5 cm)	▶ Voodoo Trac 26" x 12" - 12" (66 x 30.5 - 30.5 cm)				
Caster Tires	15" x 6.5" - 6" Pneumatic (38 x 16.5 - 15.2 cm)		15" x 6.5" - 6" Pneumatic (38 x 16.5 - 15.2 cm)					
Fuel/Capacity	Gas/10-Gal (37.9 L)		Gas/10-Gal (37.9 L)					
Digital Hour Meter	Standard		Standard					
Hydraulic Drive System	ZT-4400 Integrated Pumps & Wheel Motors		ZT-4400 Integrated Pumps & Wheel Motors					
Maximum Forward Speed	12 mph (19.3 km/h)		12 mph (19.3 km/h)					
Clutch	Electromagnetic		Electromagnetic					
MOWING DECKS								
Deck Size	52" (132.1 cm)	▶ 60" (152.4 cm)	52" (132.1 cm)	▶ 60" (152.4 cm)	▶ 60" (152.4 cm)			
Cutting Deck	7-Gauge TURBO FORCE		7-Gauge TURBO FORCE					
Deck Lift Design	Extension Spring		Standard					
Spindle Housings	9" (22.9 cm) Dia. Aluminum		9" (22.9 cm) Dia. Aluminum					
1" (2.5 cm) Spindle Shaft	Standard		Standard					
Spindle Bearings	Maintenance-Free		Maintenance-Free					
Adjustable Height of Cut Foot Pedal	Standard, 1.5" - 5.5" in .25" increments (3.8 - 14 cm in .6 cm increments)		Standard, 1.5" - 5.5" in .25" increments (3.8 - 14 cm in .6 cm increments)					
Deck Depth	5.5" (14 cm)		5.5" (14 cm)					
Blades	.204" (.5 cm) Heat-Treated Steel		.204" (.5 cm) Heat-Treated Steel					
Blade Tip Speed	18,500+ ft/min		18,500+ ft/min					
Belt Construction	Aramid Fiber V-Belt		Aramid Fiber V-Belt					
FEATURES								
MyRIDE® Suspension System			▶ MyRIDE Suspension System					
Comfort Platform	N/A							
Platform Travel	N/A		3.0" (7.62 cm)					
Shocks	N/A		1 center / 2 rear					
Seat	N/A		High-Back Comfort					
Adjustability	N/A		5 Detents, Infinite Adjustability					
2" Hitch Receiver	Standard		Standard					
Steering Controls	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened		1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened					
Operator Seat	Deluxe Suspension with Armrests		Deluxe Comfort with Armrests					
LED Lights	Standard		Standard					
Step-Through Floorpan	Standard		N/A					
Electric Deck Lift Assist	Optional		▶ Standard		Optional			
Smart Hour Meter & USB	Standard		Standard					
Warranty**	5-Year 1250-Hour 2-Year No Hour Limit		5-Year 1250-Hour 2-Year No Hour Limit					
WEIGHTS AND MEASUREMENTS								
Weight	1,085 lbs.	492.1 kg	1,185 lbs.	537.5 kg	1,185 lbs.	537.5 kg	1,317 lbs.	597.4 kg
Deck Clearance Width	53.7"	136.4 cm	61.7"	156.7 cm	61.7"	156.7 cm	61.7"	156.7 cm
Deflector Width	67.6"	171.7 cm	75.7"	192.3 cm	75.7"	192.3 cm	75.7"	192.3 cm
Length	79.2"	201.2 cm	83.1"	211.1 cm	83.1"	211.1 cm	83.1"	211.1 cm

PRIDE CUT IN EVERY PASS

Constructed with high-strength materials and engineered with proven technologies, the TURBO FORCE cutting deck is built from 100 years of experience and over 100 million unrelenting hours of real-world results.

A BEAST FOR BEAUTY

Every Z Master 4000 is loaded with a heavy-duty front-end design, TURBO FORCE deck with bullnose bumper, and pro-grade engine transforming a battlefield of brutal vegetation into a pristine pro cut.

GET COMFORTABLE CRUSHING IT

Keep mowing full blast in full-time comfort with a deluxe suspension seat. Or get battle-ready with the MyRIDE® Suspension System.

	PRO				HDX PRO													
	74000	74002	74004	74035	74010 HDX Pro	74015 HDX Pro	74020 HDX Pro XL	74022 HDX Pro XL	74024 HDX Pro XL									
POWER SYSTEM																		
Commercial Engines at 3600 RPM*	24.5 Kawasaki® FX751 (852cc)	▶ 25.5 Kawasaki FX801V (852cc)		▶ 26.5 hp Kohler Command Pro EFI (747cc)	▶ 31 hp Kawasaki FX921V (999cc)		▶ 35 hp Kawasaki FX1000 (999cc)											
Starter	Electric				Electric													
Heavy-Duty Canister Air Cleaner	Standard				Standard													
Drive Tires	24" x 9.5" – 12" (61 x 24.1 – 30.5 cm)	24" x 10.5" – 12" (61 x 26.7 – 30.5 cm)	24" x 12" – 12" (61 x 30.5 – 30.5 cm)		24" x 10.5" – 12" (61 x 26.7 – 30.5 cm)	▶ 24" x 12" – 12" (61 x 30.5 – 30.5 cm)	▶ Super Turf 26" x 12" – 12" (66 x 30.5 – 30.5 cm)		▶ Voodoo Trac 26" x 12" – 12" (66 x 30.5 – 30.5 cm)									
Caster Tires	13" x 6.5" - 6" Flat-Free Semi-Pneumatic (33 x 16.5 – 15.2 cm)				13" x 6.5" - 6" Flat-Free Semi-Pneumatic (33 x 16.5 – 15.2 cm)	▶ 15" x 6.5" - 6" Flat-Free Semi-Pneumatic (38.1 x 16.5 – 15.2 cm)												
Fuel/Capacity	Gas/10-Gal (37.9 L)				Gas/10-Gal (37.9 L)													
Digital Hour Meter	Standard				Standard													
Hydraulic Drive System	ZT-4400 Integrated Pumps & Wheel Motors				▶ ZT-5400 Integrated Pumps & Wheel Motors													
Maximum Forward Speed	10 mph (16.1 km/h)				▶ 12 mph (19.3 km/h)													
Clutch	Electromagnetic				Electromagnetic													
MOWING DECKS																		
Deck Size	48" (121.9 cm)	▶ 52" (132.1 cm)	▶ 60" (152.4 cm)	60" (152.4 cm)	52" (132.1 cm)	▶ 60" (152.4 cm)	60" (152.4 cm)	▶ 72" (182.9 cm)	▶ 72" (182.9 cm)									
Cutting Deck	7-Gauge TURBO FORCE				7-Gauge TURBO FORCE													
Deck Lift Design	Extension Spring				Extension Spring													
Spindle Housings	9" (22.9 cm) Dia. Aluminum				9" (22.9 cm) Dia. Aluminum													
1" (2.5 cm) Spindle Shaft	Standard				Standard													
Spindle Bearings	Maintenance-Free				Maintenance-Free													
Adjustable Height of Cut	Standard, 1.5" - 5.5" in .25" increments (3.8 – 14 cm in .6 cm increments)				Standard, 1.5" - 5.0" in .25" increments (3.8 – 12.7 cm in .6 cm increments)													
Foot Pedal	5.5" (14 cm)				5.5" (14 cm)													
Blades	.204" (.5 cm) Heat-Treated Steel				.204" (.5 cm) Heat-Treated Steel													
Blade Tip Speed	18,500+ ft/min				18,500+ ft/min													
Belt Construction	Aramid Fiber V-Belt				Aramid Fiber V-Belt													
FEATURES																		
MyRIDE® Suspension System									▶ MyRIDE Suspension System									
Comfort Platform	N/A				N/A				3.0" (7.62 cm)									
Platform Travel	N/A				N/A				1 center / 2 rear									
Shocks	N/A				N/A				High-Back Comfort									
Seat	N/A				N/A				5 Detents, Infinite Adjustability									
Adjustability	N/A				N/A													
2" Hitch Receiver	Standard				Standard		N/A		N/A									
Steering Controls	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened				1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened													
Operator Seat	Deluxe Suspension with Armrests				Deluxe Suspension with Armrests				Deluxe Comfort with Armrests									
LED Lights	Optional				Optional													
Step-Through Floorpan	▶ Standard				Standard													
Electric Deck Lift Assist	Optional				Optional													
Smart Hour Meter & USB	Standard				Standard													
Warranty**	5-Year 1250-Hour 2-Year No Hour Limit				▶ 5-Year 1500-Hour 2-Year No Hour Limit													
WEIGHTS AND MEASUREMENTS																		
Weight	1,048 lbs.	475.4 kg	1,085 lbs.	492.1 kg	1,185 lbs.	537.5 kg	1,185 lbs.	537.5 kg	1,085 lbs.	492.1 kg	1,185 lbs.	537.5 kg	1,360 lbs.	616.9 kg	1,300 lbs.	589.7 kg	-	-
Deck Clearance Width	49.7"	126.2 cm	53.7"	136.4 cm	61.7"	156.7 cm	61.7"	156.7 cm	53.7"	136.4 cm	61.7"	156.7 cm	65.5"	166.4 cm	75.6"	192.0 cm	75.6"	192.0 cm
Deflector Width	63.6"	161.5 cm	67.6"	171.7 cm	75.7"	192.3 cm	75.7"	192.3 cm	67.6"	171.7 cm	75.7"	192.3 cm	75.3"	191.3 cm	87.6"	222.5 cm	87.6"	222.5 cm
Length	79.2"	201.2 cm	79.2"	201.2 cm	83.1"	211.1 cm	83.1"	211.1 cm	79.2"	201.2 cm	83.1"	211.1 cm	86.5"	219.7 cm	89.3"	226.8 cm	89.3"	226.8 cm

*The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower. **See your local Toro dealer or consult owners manual for complete warranty details.

▶ = Step Up Feature



NOW AVAILABLE
Triple/DFS bagger
for HDX PRO XL models

PERFECT ONE-PASS CUTTING

The TURBO FORCE® Cutting Deck: enhances the after-cut appearance through dual capture anti-scalp rollers, rubber discharge chute, a clear sight-line to rear tires and the offset 7-gauge steel deck.

4.4–6.6 Maximum Acres/Hour

Maximum acres per hour based on 90% efficiency (MPH x width of cut). Actual productivity dependent upon conditions.



NO MESSING AROUND

Pairing the durable rugged I-beam front end, along with the TURBO FORCE deck's bullnose bumper and heavy-duty cast aluminum spindle housings, durability is king.



MyRIDE® SUSPENSION SYSTEM

Take it to the next level of comfort with the industry's only adjust-on-the-fly rear suspension with beefy shocks featuring up to 3 inches of travel to soak up what Mother Nature puts in your path.



MOW ON AND ON

4000s come with conveniences like the optional electronic deck lift assist, to front step thru deck, and USB ports.

Z MASTER®

5000 SERIES

SEE PAGE 2 FOR BATTERY
REVOLUTION SERIES OPTIONS



PRODUCTIVE FROM TOP TO BOTTOM.



HORIZON360
CONTRACTOR BUSINESS SOFTWARE

COMPATIBLE

Z MASTER® 5000 SERIES

72906†

LIMITED QUANTITY

72907

72908 CARB

POWER SYSTEM

Commercial Engines at 3600 RPM*	25 hp Kohler® Command PRO EFI (747cc)
Starter	Electric
Heavy-Duty Canister Air Cleaner	Standard
Drive Tires	23" x 9.5" – 12" (58.4 x 24.1 – 30.5 cm)
Caster Tires	13" x 6.5" – 6" Flat-Free Semi-Pneumatic (33 x 16.5 – 15.2 cm)
Fuel/Capacity	Gas/12-Gal (45.4 L)
Hour Meter	Standard
Hydraulic Drive System	Unitized Pump & Wheel Motors
Pump	12cc/re (shock valves)
Wheel Motor	14.6 cir
Maximum Forward Speed	10 mph (16.1 km/h)
Clutch	Electromagnetic

MOWING DECKS

Deck Size	52" (132.1 cm)
Cutting Deck	7-Gauge TURBO FORCE
Bullnose Bumper	Standard
Adjustable Discharge Baffle	Standard
Rubber Discharge Chute	Standard
Spindle Housings	9" (22.9 cm) Diameter Cast Aluminum
Spindle Bearings	Maintenance-Free
Cutting Height	1.0" – 5.5" (2.5 – 14 cm)
Blades	.204" (.5 cm) Heat-Treated Steel
Blade Tip Speed	18,500+ ft/min
Belt Construction	Aramid Fiber V-Belt
Anti-Scalp Rollers	3 Standard, 1 Optional 2 Side Bumpers/4 Rollers
Carrier Frame Construction	3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge)

FEATURES

Steering Controls	1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened
Operator Seat	Deluxe Suspension with 3-D Isolation Mounts
Armrests	Standard
Seat Suspension System	Standard
Folding ROPS	Standard
Storage Compartment	Standard
Foot Pedal Deck Lift	Standard
Z Stand	Optional
Floor Pan	Pierced, Extruded Tread; No-Tools Deck Access

WEIGHTS AND MEASUREMENTS

Weight	1,168 lbs.	529.8 kg	1,335 lbs.	605.5 kg
ROPS Height (Folded)	46.8"	118.9 cm	46.8"	118.9 cm
ROPS Height (Upright)	70.5"	179.1 cm	70.5"	179.1 cm
Deck Clearance Width	53.7"	136.4 cm	78.3"	198.9 cm
Deflector Width	67.6"	171.7 cm	67.6"	171.7 cm
Length	79.2"	201.2 cm	87.3"	221.7 cm

4.4–6.5

Maximum Acres/Hour

Based on 90% efficiency (MPH x width of cut).
Actual productivity dependent upon conditions.

When you cover a lot of ground, you need a machine that keeps up. Toro's Z Master 5000 Series packs the power, fuel efficiency and comfort you demand.

	Z MASTER® 5000 SERIES											
	MyRIDE® SUSPENSION SYSTEM							MyRIDE® SUSPENSION SYSTEM				
	72957		72910		72930		72911 <i>LIMITED QUANTITY</i>		72951 <i>LIMITED QUANTITY</i>			
POWER SYSTEM	NEW											
Commercial Engines at 3600 RPM*	26.5 hp Kohler Command PRO EFI (747cc)		25.5 hp Kawasaki® FX801		25 hp Kohler Command PRO EFI (747cc)							
Starter					Electric							
Heavy-Duty Canister Air Cleaner					Standard							
Drive Tires	24" x 12" – 12" Turfmaster (61 x 30.5 – 30.5 cm)		24" x 12" – 12" (61 x 30.5 – 30.5 cm)				▶ 24" x 12" – 12" Tweels (61 x 30.5 – 30.5 cm) ▶		24" x 12" – 12" (61 x 30.5 – 30.5 cm)			
Caster Tires					13" x 6.5" – 6" Flat-Free Semi-Pneumatic (33 x 16.5 – 15.2 cm)							
Fuel/Capacity					Gas/12-Gal (45.4 L)							
Hour Meter					Standard							
Hydraulic Drive System					Unitized Pump & Wheel Motors							
Pump					12cc/re (shock valves)							
Wheel Motor					14.6 cir							
Maximum Forward Speed					10 mph (16.1 km/h)							
Clutch					Electromagnetic							
MOWING DECKS												
Deck Size	▶ 60" (152.4 cm)		▶ 60" (152.4 cm)		60" (152.4 cm)		60" (152.4 cm)		60" (152.4 cm)			
Cutting Deck					7-Gauge TURBO FORCE							
Bullnose Bumper					Standard							
Adjustable Discharge Baffle					Standard							
Rubber Discharge Chute					Standard							
Spindle Housings					9" (22.9 cm) Diameter Cast Aluminum							
Spindle Bearings					Maintenance-Free							
Cutting Height					1.0" – 5.5" (2.5 – 14 cm)							
Blades					.204" (.5 cm) Heat-Treated Steel							
Blade Tip Speed					18,500+ ft/min							
Belt Construction					Aramid Fiber V-Belt							
Anti-Scalp Rollers	2 Side Bumpers/4 Rollers						4 Standard, 1 Optional		▶ 6 Standard, 1 Optional			
Carrier Frame Construction					3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge)							
FEATURES												
Steering Controls					1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened							
Operator Seat	▶ MyRIDE Suspension System							Deluxe Suspension with 3-D Isolation Mounts			▶ MyRIDE Suspension System	
Armrests					Standard							
Seat Suspension System					Standard							
Folding ROPS					Standard							
Storage Compartment					Standard							
Foot Pedal Deck Lift					Standard							
Z Stand					Optional							
Floor Pan	Pierced, Extruded Tread; No-Tools Deck Access											
WEIGHTS AND MEASUREMENTS												
Weight	1,335 lbs.	605.5 kg	1,216 lbs.	551.6 kg	1,255 lbs.	569.3 cm	1,255 lbs.	569.3 cm	1,304 lbs.	591.5 cm		
ROPS Height (Folded)	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm		
ROPS Height (Upright)	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm		
Deck Clearance Width	78.3"	198.9 cm	61.7"	156.7 cm	61.7"	156.7 cm	61.7"	156.7 cm	61.7"	156.7 cm		
Deflector Width	N/A	N/A	75.7"	192.3 cm	75.7"	192.3 cm	75.7"	192.3 cm	75.7"	192.3 cm		
Length	87.3"	221.7 cm	83.1"	211.1 cm	83.1"	211.1 cm	83.1"	211.1 cm	83.1"	211.1 cm		

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower. †CARB compliant model or model available.

▶ = Step Up Feature



COMFORTABLE RIDE

The deluxe suspension seat features thick cushions, large bolsters and 3-D isolator mounts that absorb bumps and vibrations to reduce operator fatigue.



KEEP TABS WITH HORIZON360

Know your mower's GPS location and view battery status, daily runtime and estimated runtime from anywhere with Horizon360 Connect.



EFI FUEL EFFICIENCY

The environmentally friendly design exceeds requirements for CARB Tier III and EPA Phase III, and keeps emissions as low as possible by continuing to run at optimal levels.



HIGH-STRENGTH BLADES

Pick your performance. Match the blade to the job for an outstanding cut everytime.

Z MASTER® 5000 SERIES (CONTINUED)

MyRIDE® SUSPENSION SYSTEM

72918

72912
LIMITED QUANTITY

72953†

72955

72956

POWER SYSTEM

Commercial Engines
at 3600 RPM*

► 26.5 hp Kohler
Command PRO EFI (747cc)

25 hp Kohler Command
PRO EFI (747cc)

26.5 hp Kohler Command
PRO EFI (747cc)

Starter

Electric

Heavy-Duty Canister
Air Cleaner

Standard

Drive Tires

24" x 12" – 12"
(61 x 30.5 – 30.5 cm)

24" x 12" – 12"
Tweels
61 x 30.5 – 30.5 cm

24" x 12" – 12" Turfmaster
(61 x 30.5 – 30.5 cm)

23" x 9.5" – 12"
(58.4 x 24.1 – 30.5 cm)

24" x 12" – 12" Turfmaster
(61 x 30.5 – 30.5 cm)

Caster Tires

13" x 6.5" – 6" Flat-Free Semi-Pneumatic
(33 x 16.5 – 15.2 cm)

Fuel/Capacity

Gas/12-Gal (45.4 L)

Hour Meter

Standard

Hydraulic Drive System

Unitized Pump & Wheel Motors

Pump

12cc/re (shock valves)

Wheel Motor

14.6 cir

Maximum Forward Speed

10 mph (16.1 km/h)

Clutch

Electromagnetic

MOWING DECKS

Deck Size

► 72" (182.9 cm)

72" (182.9 cm)

60" (152.4 cm)

52" (132.1 cm)

52" (132.1 cm)

Cutting Deck

7-Gauge TURBO FORCE

Bullnose Bumper

Standard

Adjustable Discharge Baffle

Standard

Rubber Discharge Chute

Standard

Spindle Housings

9" (22.9 cm) Diameter Cast Aluminum

Spindle Bearings

Maintenance-Free

Cutting Height

1.0" – 5.5" (2.5 – 14 cm)

Blades

204" (.5 cm) Heat-Treated Steel

Blade Tip Speed

18,500+ ft/min

Belt Construction

Aramid Fiber V-Belt

Anti-Scalp Rollers

► 6 Standard, 1 Optional

2 Side Bumpers/4 Rollers

Carrier Frame Construction

3" x 1.5" x 10-Gauge (.76 cm x 3.8 cm x 10-Gauge)

FEATURES

Steering Controls

1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened

Operator Seat

Deluxe Suspension with
3-D Isolation Mounts

► MyRIDE Suspension System

Armrests

Standard

Seat Suspension System

Standard

Folding ROPS

Standard

Storage Compartment

Standard

Foot Pedal Deck Lift

Standard

Z Stand

Optional

Floor Pan

Pierced, Extruded Tread; No-Tools Deck Access

WEIGHTS AND MEASUREMENTS

Weight	1,296 lbs.	587.9 kg	1,296 lbs.	587.9 kg	1,335 lbs.	605.5 kg	1,259 lbs.	571 kg	1,335 lbs.	605.5 kg
ROPS Height (Folded)	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm
ROPS Height (Upright)	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm
Deck Clearance Width	61.7"	156.7 cm	61.7"	156.7 cm	78.3"	198.9 cm	53.7"	136.4 cm	78.3"	198.9 cm
Deflector Width	75.7"	192.3 cm	75.7"	192.3 cm	75.7"	192.3 cm	67.6"	171.7 cm	75.7"	192.3 cm
Length	83.1"	211.1 cm	83.1"	211.1 cm	87.3"	221.7 cm	79.2"	201.2 cm	87.3"	221.7 cm

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower. †CARB compliant model or model available.

► = Step Up Feature

Z MASTER®

5000 SERIES REAR DISCHARGE

SEE PAGE 2 FOR BATTERY
REVOLUTION® SERIES OPTIONS



HORIZON360®
CONTRACTOR BUSINESS SOFTWARE

COMPATIBLE

NEED A PRODUCTIVITY EDGE?

Our rear discharge models let operators trim on either side of the deck while keeping sidewalks and flowerbeds clipping-free.

SAVE TIME AND CLEANUP

With the rear discharge deck design that drops clippings within the path of the mower, gain fuel efficiency with Kohler® Command PRO® engines featuring electronic fuel injection (EFI).



MICHELIN® TWEELS® AIRLESS RADIAL TURF TIRES

No maintenance, no compromise, no downtime. Compatible with many models - now including CASTER options!



REAR DISCHARGE

Two blades rotate clockwise and one blade rotates counter-clockwise to spread clippings evenly through the rear discharge tunnel, saving time and cleanup.



ANTI-SCALPING SYSTEM

Durable, adjustable side bumpers protect the mower while enhancing deck flotation over uneven surfaces.



RUGGED PERFORMANCE

Highly productive in taller grass and weed conditions.

ZMASTER® 5000 SERIES REAR DISCHARGE

72921†
LIMITED QUANTITY

72922†

72923

72924 CARB

POWER SYSTEM

Commercial Engines at 3600 RPM*	25 hp Kohler Command PRO EFI (747cc)	26.5 hp Kohler Command PRO EFI (747cc)	25 hp Kohler Command PRO EFI (747cc)
Starter	Electric		
Heavy-Duty Canister Air Cleaner	Standard		
Drive Tires	24" x 12" - 12" Michelin® Tweels (61 x 30.5 - 30.5 cm)		
Caster Tires	13" x 6.5" - 6" Flat-Free Semi-Pneumatic (33 x 16.5 - 15.2 cm)		
Fuel/Capacity	Gas/12-Gal (45.4 L)		
Hour Meter	Standard		
Hydraulic Drive System	Unitized Pumps & Wheel Motors		
Pump	12cc/rev (shock valves)		
Wheel Motor	14.6 cir		
Maximum Forward Speed	10 mph (16.1 km/h)		
Clutch	Electromagnetic		

MOWING DECKS

Deck Size	60" (152.4 cm)	▶ 72" (182.9 cm)	60" (152.4 cm)
Cutting Deck	7-Gauge TURBO FORCE Rear Discharge		
Bullnose Bumper	Standard		
Deck Lift Design	Extension Spring		
Spindle Housings	9" (22.9 cm) Diameter Cast Aluminum		
1" (2.5 cm) Heavy-Duty Spindle Shaft	Standard		
Spindle Bearings	Maintenance-Free		
Cutting Height	1.0" - 5.5" (2.5 - 14 cm)		
Blades	.204" (.5 cm) Heat-Treated Steel		
Blade Tip Speed	18,500+ ft/min		
Belt Construction	Aramid Fiber V-Belt		
Anti-Scalp Rollers	2 Side Bumpers/4 Rollers		
Carrier Frame Construction	3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge)		

FEATURES

Steering Controls	1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened
Operator Seat	Deluxe Suspension with 3-D Isolation Mounts
Armrests	Standard
Seat Suspension System	Standard
Folding ROPS	Standard
Storage Compartment	Standard
Foot Pedal Deck Lift	Standard
Z Stand	Optional
Floor Pan	Pierced, Extruded Tread; No-Tools Deck Access

WEIGHTS AND MEASUREMENTS

Weight	1,335 lbs.	605.5 kg	1,335 lbs.	605.5 kg	1,335 lbs.	605.5 kg
ROPS Height (Folded)	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm
ROPS Height (Upright)	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm
Deck Clearance Width	78.3"	198.9 cm	78.3"	198.9 cm	78.3"	198.9 cm
Deflector Width	N/A	N/A	N/A	N/A	N/A	N/A
Length	87.3"	221.7 cm	87.3"	221.7 cm	87.3"	221.7 cm

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower. †CARB compliant model.

▶ = Step Up Feature

Z MASTER®

6000 SERIES

SEE PAGE 2 FOR BATTERY
REVOLUTION SERIES OPTIONS

OWN THE MOWER THAT OWNS EVERY JOB.



HORIZON360®
CONTRACTOR BUSINESS SOFTWARE

COMPATIBLE

	ZMASTER® 6000 SERIES															
						MyRIDE® SUSPENSION SYSTEM		MyRIDE® SUSPENSION SYSTEM								
	72926		72960		72965		72967		72968		72928		72961			
POWER SYSTEM																
Commercial Engines at 3600 RPM*	26.5 hp Kohler® Command PRO EFI (747cc)				▶ 31 hp Kawasaki® FX (999cc)						26.5 hp Kohler Command PRO EFI (747cc)		31 hp Kawasaki FX (999cc)			
Electric Start							Standard									
Heavy-Duty Canister Air Cleaner							Standard									
Drive Tires	24" x 12" – 12" (61 x 30.5 – 30.5 cm)				▶ 24" x 12" – 12" Michelin® Tweels (61 x 30.5 – 30.5 cm)				24" x 12" – 12" (61 x 30.5 – 30.5 cm)							
Caster Tires							13" x 6.5" – 6" Flat-Free Semi-Pneumatic (33 x 16.5 – 15.2 cm)									
Fuel/Capacity							Gas/12-Gal (45.4 L)									
Hour Meter							Standard									
Hydraulic Drive System							Unitized Pumps & Wheel Motors									
Pump							16cc/rev									
Wheel Motor							17.1 cir									
Maximum Forward Speed							11.5 mph (18.5 km/h)									
Clutch							Electromagnetic									
MOWING DECKS																
Deck Size	60" (152.4 cm)		60" (152.4 cm)		60" (152.4 cm)		60" (152.4 cm)		72" (182.9 cm)		72" (182.9 cm)		72" (182.9 cm)			
Cutting Deck							7-Gauge TURBO FORCE®									
Bullnose Bumper							Standard									
Adjustable Discharge Baffle							Standard, Tools-Free									
Rubber Discharge Chute							Standard									
Deck Lift Design							Extension Spring									
Spindle Housings							9" (22.9 cm) Diameter Cast Aluminum									
1" (2.5 cm) Heavy-Duty Spindle Shaft							Standard									
Spindle Bearings							Maintenance-Free									
Cutting Height							1.0" – 5.5" (2.5 cm – 14 cm)									
Blades							.204" (.5 cm) Heat-Treated Steel									
Blade Tip Speed							18,500+ ft/min									
Belt Construction							Aramid Fiber V-Belt									
Anti-Scalp Rollers							4 Standard, 1 Optional									
Carrier Frame Construction							3" x 1.5" – 10-Gauge (7.6 x 3.8 cm)									
FEATURES																
Steering Controls							1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened									
Operator Seat	Deluxe Suspension w/ 3-D Isolation Mounts						▶ MyRIDE Suspension System				Deluxe Suspension w/ 3-D Isolation Mounts					
Armrests							Standard									
Seat Suspension System							Standard									
Folding ROPS							Standard									
Storage Compartment							Standard									
Foot Pedal Deck Lift							Standard									
Z Stand							Optional									
Floor Pan							Pierced, Extruded Tread; No-Tools Deck Access									
WEIGHTS AND MEASUREMENTS																
Weight	1,254 lbs.	568.8 kg	1,254 lbs.	568.8 kg	1,254 lbs.	568.8 kg	1,370 lbs.	621.4 kg	1,289 lbs.	584.7 kg	1,350 lbs.	612.3 kg	1,334 lbs.	605.1 kg		
ROPS Height (Folded)	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm		
ROPS Height (Upright)	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm		
Deck Clearance Width	61.7"	156.7 cm	61.7"	156.7 cm	61.7"	156.7 cm	61.7"	156.7 cm	61.7"	156.7 cm	73.6"	186.9 cm	73.6"	186.9 cm		
Deflector Width	75.7"	192.3 cm	75.7"	192.3 cm	75.7"	192.3 cm	75.7"	192.3 cm	75.7"	192.3 cm	87.6"	222.5 cm	87.6"	222.5 cm		
Length	83.1"	211.1 cm	83.1"	211.1 cm	83.1"	211.1 cm	83.1"	211.1 cm	83.1"	211.1 cm	86.1"	218.7 cm	86.1"	218.7 cm		



MYRIDE® SUSPENSION SYSTEM

The MyRIDE Suspension System features a rear shock adjustable operator platform that isolates bumps and vibrations.

Models 72967 and 72968 only. See pages 8-9 for details.



HORIZON™ TECHNOLOGY

Choose the performance mode to increase productivity and reduce fuel consumption.

Models 72969, 72946 and 72947 only. See page 10 for details.



PRO RESULTS EVERY TIME

TURBO FORCE® 5.5" deep cutting decks feature 18,500+ ft./min. blade tip speed and nearly 1/4" thick heat-treated steel blades.



DECK LIFT ASSIST

Standard deck lift assist foot pedal allows operator to adjust the deck height quickly and easily.

	ZMASTER™ 6000 SERIES															
	HORIZON™ TECHNOLOGY		HORIZON™ TECHNOLOGY													
	72946 LIMITED QUANTITY		72947 LIMITED QUANTITY		72976		72977		72980 LIMITED QUANTITY		72981		72982 LIMITED QUANTITY		72983	
POWER SYSTEM					NEW		NEW				NEW				NEW	
Commercial Engines at 3600 RPM*			▶ 38 hp Kohler Command PRO EFI (999cc)						▶ 37 hp Vanguard Oil Guard (993cc)		▶ 37 hp Vanguard EFI (993cc) ETC Oil Guard		▶ 37 hp Vanguard Oil Guard (993cc)		▶ 37 hp Vanguard EFI (993cc) ETC Oil Guard	
Electric Start							Standard									
Heavy-Duty Canister Air Cleaner							Standard									
Drive Tires			24" x 12" – 12" (61 x 30.5 – 30.5 cm)								Super Turf 24" x 12" – 12" (61 x 30.5 – 30.5 cm)					
Caster Tires							13" x 6.5" – 6" Flat-Free Semi-Pneumatic (33 x 16.5 – 15.2 cm)									
Fuel/Capacity							Gas/12-Gal (45.4 L)									
Hour Meter	▶ Horizon Technology						Standard									
Hydraulic Drive System							Unitized Pumps & Wheel Motors									
Pump							16cc/rev									
Wheel Motor							17.1 cir									
Maximum Forward Speed			11.5 mph (18.5 km/h)								▶ 12 mph (19.3 km/h)					
Clutch							Electromagnetic									
MOWING DECKS																
Deck Size	60" (152.4 cm)		72" (182.9 cm)		60" (152.4 cm)		▶ 72" (182.9 cm)		60" (152.4 cm)		60" (152.4 cm)		▶ 72" (182.9 cm)		▶ 72" (182.9 cm)	
Cutting Deck							7-Gauge TURBO FORCE™									
Bullnose Bumper							Standard									
Adjustable Discharge Baffle							Standard, Tools-Free									
Rubber Discharge Chute							Standard									
Deck Lift Design							Extension Spring									
Spindle Housings							9" (22.9 cm) Diameter Cast Aluminum									
1" (2.5 cm) Heavy-Duty Spindle Shaft							Standard									
Spindle Bearings							Maintenance-Free									
Cutting Height							1.0" – 5.5" (2.5 cm – 14 cm)									
Blades							.204" (.5 cm) Heat-Treated Steel									
Blade Tip Speed							18,500+ ft/min									
Belt Construction							Aramid Fiber V-Belt									
Anti-Scalp Rollers							4 Standard, 1 Optional						▶ 6 Standard, 1 Optional			
Carrier Frame Construction							3" x 1.5" – 10-Gauge (7.6 x 3.8 cm)									
FEATURES																
Steering Controls							1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened									
Operator Seat							Deluxe Suspension w/ 3-D Isolation Mounts									
Armrests							Standard									
Seat Suspension System							Standard									
Folding ROPS							Standard									
Storage Compartment							Standard									
Foot Pedal Deck Lift							Standard									
Z Stand							Optional									
Floor Pan							Pierced, Extruded Tread; No-Tools Deck Access									
WEIGHTS AND MEASUREMENTS																
Weight	1,440 lbs.	653.2 kg	1,369 lbs.	621 kg	1,440 lbs.	653.2 kg	1,369 lbs.	621 kg	1,447 lbs.	656 kg	1,447 lbs.	656 kg	1,644 lbs.	746 kg	1,644 lbs.	746 kg
ROPS Height (Folded)	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm
ROPS Height (Upright)	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm
Deck Clearance Width	73.6"	186.9 cm	73.6"	186.9 cm	73.6"	186.9 cm	73.6"	186.9 cm	61.7"	156.7 cm	61.7"	156.7 cm	73.6"	186.9 cm	73.6"	186.9 cm
Deflector Width	87.6"	222-.5 cm	87.6"	222.5 cm	87.6"	222-.5 cm	87.6"	222.5 cm	75.7"	192.3 cm	75.7"	192.3 cm	87.6"	222.5 cm	87.6"	222.5 cm
Length	86.1"	218.7 cm	86.1"	218.7 cm	86.1"	218.7 cm	86.1"	218.7 cm	83.1"	211.1 cm	83.1"	211.1 cm	86.1"	218.7 cm	86.1"	218.7 cm

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

Z MASTER®

7500 SERIES

MASSIVE 144-INCH WING-DECK



MASSIVE 144-INCH WINGSPAN REDEFINES PRODUCTIVITY

Step up your productivity with the Toro Z Master 7500-D. The NEW 144" deck folds up neatly to only 83" for fast and easy transport up to 17 MPH, then folds down to handle your biggest jobs in less time than comparable mowers. Powerful engines deliver all the speed and maneuverability of a zero-turn, along with the superior cut quality you expect from Toro.

POWER THROUGH

The toughest mowing jobs with a Yanmar diesel engine or Kohler 38 HP* gas engine.

MAXIMIZE PRODUCTIVITY

With side and rear discharge commercial cutting decks ranging from 60 to 144 inches.

MOW SMARTER

With Horizon™ Technology that lets you choose the right operating mode for the conditions, saving fuel costs while maintaining top-level performance.

RIDE IN COMFORT

With the iso-mounted floor pan and deluxe suspension iso-mount seat that dramatically reduce vibration for less operator downtime and more productivity.



CONTOUR-FOLLOWING WING DECKS

Wing decks on the 96" model flex up 20° and down 15° to follow the terrain, hugging the ground for the smoothest possible cut. Folds to 72.5" to fit in trailer.



THE NEW STANDARD IN COMFORT

The floor pan and deluxe suspension seat are iso-mounted to reduce vibration. That results in a better operator experience and more productivity.



EXTENDED SERVICE INTERVALS

Save on maintenance with extended service intervals and a deck design that uses up to four matching blades. The mower is also backed by a 5-year, 1,500-hour limited warranty (first two years no-hour-limit).



SUPERIOR PERFORMANCE

Whether you choose a Yanmar diesel engine or a Kohler 38 HP EFI gas engine, your mower is packed with power to tackle the toughest mowing jobs.

	ZMASTER™ 7500 SERIES																	
	HORIZON™ TECHNOLOGY																	HORIZON™ TECHNOLOGY W/ORACLE
	72028†	72029†		72027		72030		72076†		72074†		72098†		74090		72144		
POWER SYSTEM																		
Commercial Engines at 3600 RPM*	25 hp Yanmar® Diesel 1267cc								▶ 37 hp Yanmar Diesel 1642cc						▶ 38 hp Kohler® EFI		▶ 44 hp Yanmar Diesel 1568cc	
Heavy-Duty Canister Air Cleaner	Air Filtration System with Electronic Vacuum Sensor																	
Drive Tires	26" x 12" – 12" (66.0 x 30.5 x 30.5 cm)												24" x 12" – 12" (61.0 x 30.5 x 30.5 cm)		▶ 26" x 12" – 12" (66.0 x 30.5 x 30.5 cm)			
Caster Tires	15" x 6" – 6" Flat-Free Semi-Pneumatic (38.1 x 15.2 x 15.2 cm)												13" x 6.5" – 6" Flat-Free Semi-Pneumatic (33 x 16.5 x 15.2 cm)		▶ 15" x 6" – 6" Flat-Free Semi-Pneumatic (38.1 x 15.2 x 15.2 cm)			
Fuel/Capacity	Diesel/12.5-Gal (47.3 L)												Gasoline/12-Gal (45.4 L)		Diesel/12.5-Gal (47.3 L)			
Hour Meter	Horizon Technology																	
Hydraulic Drive System	17.84 cu in Hydro-Gear HGM-H Motors with 18cc Kanzaki® Pump												Unitized 16cc Pumps & Wheel Motors w/Cooling Fans		17.84 cu in Hydro-Gear HGM-H Motors with 18cc Kanzaki Pump			
Max Ground Speed (Fwd)	12.5 mph (20.1 km/h)												11.5 mph (18.5 km/h)		10/17 mph (16.1/27.4 km/h)			
Clutch	Wet Disc												Electromagnetic		Wet Disc			
MOWING DECKS																		
Deck Size	60" (152.4 cm) (Rear Discharge)	▶ 72" (182.9 cm) (Rear Discharge)		60" (152.4 cm)		72" (182.9 cm)		72" (182.9 cm)		72" (182.9 cm) (Rear Discharge)		▶ 96" (243.8 cm) (Rear Discharge)		96" (243.8 cm) (Rear Discharge)		▶ 144" (365.7 cm) (Rear Discharge)		
Cutting Deck	7-Gauge TURBO FORCE™																	
Bullnose Bumper	Standard																	
Deck Depth	5.5" (14.0 cm)																	
Adjustable Discharge Baffle	N/A			Standard						N/A								
Rubber Discharge Chute	N/A			Standard						N/A								
Deck Lift Design	Hydraulic with Rocker Switch																	
Spindle Housings	9" (22.9 cm) Diameter Cast Aluminum																	
1" (2.5 cm) Heavy-Duty Spindle Shaft	Standard																	
Spindle Bearings	Maintenance-Free																	
Cutting Height	1.0" – 5.5" (2.5 – 14.0 cm)																	
Blades	3 blades at 20.5" length										4 blades at 24.5" length				▶ 6 blades at 24.5" length			
Blade Tip Speed	18,200+ ft/min			▶ 18,500+ ft/min						18,100+ ft/min				18,500+ ft/min				
Shaft Drive	Standard																	
Anti-Scalp Rollers	4 Standard, 2 Side Skids			6 Standard						4 Standard, 2 Side Skids		13 Standard						
FEATURES																		
Steering Controls	1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened																	
Operator Seat	Deluxe Suspension (Iso-Mount, Flip-Up)																	
Armrests	Standard																	
Seat Suspension System	Standard																	
Folding ROPS	Standard																	
Cooling Fans	N/A															▶ Standard		
Storage Compartment	Standard																	
Floor Pan	Flip-Up, Iso-Mount																	
WEIGHTS AND MEASUREMENTS																		
Weight	1,957 lbs.	887.7 kg	1,964 lbs.	890.9 kg	1,987 lbs.	901.3 kg	2,047 lbs.	928.5 kg	2,067 lbs.	937.5 kg	2,143 lbs.	972 kg	2,650 lbs.	1,202 kg	2,584 lbs.	1,172 kg	3,270 lbs.	1,483 kg
ROPS Height (Folded)	51"	129.5 cm	51"	129.5 cm	51"	129.5 cm	51"	129.5 cm	51"	129.5 cm	51"	129.5 cm	51"	129.5 cm	51"	129.5 cm	51"	129.5 cm
ROPS Height (Upright)	71.8"	182.4 cm	71.8"	182.4 cm	71.8"	182.4 cm	71.8"	182.4 cm	71.8"	182.4 cm	71.8"	182.4 cm	71.8"	182.4 cm	71.8"	182.4 cm	71.8"	182.4 cm
Deck Width	66.3"	186.4 cm	78.3"	198.9 cm	61.4"	156.0 cm	73.4"	186.4 cm	73.6"	186.9 cm	78.3"	198.9 cm	102.3"	259.8 cm	102.3"	259.8 cm	144.9"	368.1 cm
Deck Width - Wings Up	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	73"	185.4 cm	73"	185.4 cm	83"	210.8 cm
Deflector Width	N/A	N/A	N/A	N/A	72.8"	184.9 cm	84.9"	215.6 cm	87.6"	222.5 cm	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Length	96.48"	245.1 cm	100.68"	255.7 cm	99.68"	245.1 cm	99.6"	253.0 cm	99.68"	245.1 cm	100.68"	255.7 cm	97.38"	247.3 cm	97.38"	247.3 cm	101.3"	257.3 cm

* The gross horsepower of these diesel engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower. † CARB compliant model or model available.

▶ = Step Up Feature

8000 SERIES

DIRECT COLLECT Z



For high-end properties, a clean, manicured look is everything. 8000 Series Direct Collect Z gives you that and more. A powerful blower moves more air, throwing large volumes of material into the hopper while the high-capacity collection system helps extend mowing time. This machine is built to give you everything you need to achieve the perfect cut in less time.

TRIM ON BOTH SIDES

With the rear direct collect deck to keep flower beds and walkways clipping-free.

SLICE GRASS INTO FINE PARTICLES

With a higher blade tip speed and optimal mulching kits for a consistent, quality cut.

REDUCE DOWNTIME

With features that minimize maintenance including a heavy-duty sealed gearbox and a simple, reliable belt drive system.

MOW LONGER

With the 7.5-gallon fuel tank and the high-capacity collection system for bagging and mulching for fewer stops.


GAIN PRODUCTIVITY

With a ground speed of up to 7 mph and a hydro drive system for efficient, precise control.



BAG, MULCH OR BOTH

Fill-reduction system lets you switch from 100% bagging to 50% mulching and 50% bagging, so the hopper can be emptied less frequently.



EFFORTLESS CONTROLS

No need to muscle these mowers around. The controls let you maneuver in tight spots almost effortlessly.



HIGH CAPACITY

The 9.5-bushel hopper means less time emptying and more time mowing. Exclusive baffle design fills evenly back to front for maximum efficiency.



TOUGH, DEEP DECKS

Commercial deck is made of welded 7/10-gauge steel. The deep 4-5/8" design handles taller grass and provides greater vacuum for a clean, refined cut.

THE PERFECT CUT COMES STANDARD.

	8000 SERIES DIRECT COLLECT Z			
	74316		74314	
POWER SYSTEM	74318 CARB		74319 CARB	
Commercial Engines at 3600 RPM*	25 hp Kohler® Command PRO® (725cc)		23 hp Kohler Command PRO EFI (747cc)	
Starter	Electric			
Heavy-Duty Canister Air Cleaner	Standard			
Drive Tires	18" x 10.5" – 10" (45.7 x 26.7 – 25.4 cm)			
Caster Tires	8" x 3" – 4" Semi Pneumatic (20.3 x 7.6 – 10.2 cm)			
Fuel/Capacity	Gas/7.5 Gal (28.4 L)			
Digital Hour Meter	Standard			
Hydraulic Drive System	Tandem Pumps & Wheel Motors			
Pump	12cc/rev			
Wheel Motor	18 cir			
Maximum Forward Speed	Up to 7.0 mph (11.4 km/h)			
Clutch	Mechanical (Lever-Operated)			
MOWING DECKS				
Deck Size	42" (106.7 cm)		▶ 48" (121.9 cm)	
Cutting Deck	7/10-Gauge			
Adjustable Discharge Baffle	Fill Reduction Baffles Standard			
Deck Lift Design	Manual HOC Adjustment/Spring Assisted Flip-Up			
Spindle Housings	Cast Iron Gearbox			
1" (2.5 cm) Heavy-Duty Spindle Shaft	Standard			
Cutting Height	1" – 4" (.25" increments) 2.5 – 10.2 cm (.6 cm increments)			
Blades	.164" (.417 cm) Heat-Treated Steel			
Blade Tip Speed	18,500+ ft/min			
Belt Construction	Polyester Hex Belts			
Anti-Scalp Rollers	2 Standard			
Carrier Frame Construction	2" x 1.5" x 11-Gauge (5.1 cm x 3.8 cm x 11-Gauge)			
FEATURES				
Steering Controls	Hand Control Levers			
Operator Seat	Rubber Mounted			
Seat Suspension System	Optional			
Folding ROPS	Optional			
Storage Compartment	Standard			
Floor Pan	Anti-Slip Tape, No Tools Flip-Up Deck Access			
WEIGHTS AND MEASUREMENTS				
Weight	1,140 lbs.	517.1 kg	1,170 lbs.	530.7 kg
Height	51.2"	130 cm	51.2"	130 cm
Width	43.2"	109.7 cm	49.2"	125 cm
Length	91.8"	233.2 cm	94.5"	240 cm

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995.
As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.
†CARB compliant model.

► = Step Up Feature

KEEP YOUR EQUIPMENT RUNNING LONGER WITH GENUINE TORO PARTS



**SCAN TO VIEW THE
TORO RLC PARTS
AND FITMENT GUIDE**



SUPPORT | SERVICE | GENUINE TORO PARTS

GRANDSTAND®

STAND-ON MOWERS

SEE PAGE 2 FOR BATTERY
REVOLUTION® SERIES OPTIONS



STAND UP TO ANY TERRAIN.

Bumpy patches and challenging terrain are all in a day's work—but feeling them doesn't need to be. GrandStand® combines the speed and comfort of a zero-turn rider with the on-and-off ease of a walk-behind for speed and maneuverability.

IMPROVE PRODUCTIVITY

With easy access on and off the machine—up to 10.5 gallons of fuel capacity on 48", 52", 60" and 72" models—to mow longer with fewer stops.

GAIN SPEED AND PERFORMANCE

with a new max forward ground speed of up to 12 mph and responsive solid drive linkage. (*Select models only.*)

SAVE MAINTENANCE AND TIME

With no hydraulic hoses, no daily/weekly grease points and a new engine design that allows extra room for service access. The fuel tank can also be removed without draining for easy service access to the transmission and controls.



TRACTION AND HANDLING

A wide stance and optimal balance enhance hillside stability and control. Operators can shift weight as needed to further enhance performance.



CUSHIONED SUSPENSION

Flex-Ride operator platform suspension self-compensates for operators of all sizes, resulting in less fatigue and higher productivity throughout the day.



POWERED BAGGER

Compact side-mounted soft twin bagger and vertically mounted blower allow maneuverability in tight spaces and maximum visibility.



HIGHER HORSEPOWER

Effortlessly tackle demanding jobs with an upgraded 35 hp* Kawasaki FX1000 999cc engine. (*Models 72507 and 72512*)



2-IN-1 VERSATILITY

Foldable operator platform instantly converts the machine to a walk-behind. It easily lowers back down when it's time to ride, saving time and trailer space.

GrandStand® Series helps you save time, money and trailer space with multi-season flexibility and a foldable operator platform.

2.6–5.5

Maximum Acres/Hour

Based on 90% efficiency (MPH x width of cut).
Actual productivity dependent upon conditions.

	GRANDSTAND®																
	72504		72518		72505		72519		72513		72509		72520		HDX 72506		
POWER SYSTEM	71504 CARB				71505 CARB										NEW		
Commercial Engines at 3600 RPM*	22 hp Kawasaki FX (726cc)		▶ 23 hp Kohler® Command PRO® EFI (747cc)		22 hp Kawasaki FX (726cc)		▶ 25 hp Kohler Command PRO EFI (747cc)				23.5 hp Kawasaki FX730V (726cc)		Briggs 28 HP (883cc)		31 hp Kawasaki FX921 (999cc)		
Starter	FX (726cc)															Electric	
Heavy-Duty Canister Air Cleaner	▶ Standard															▶ Standard	
Drive Tires	▶ 20" x 10.5" – 8" (50.8 x 26.7 – 20.3 cm)															▶ 24" x 9.5" – 12" Turf (61 x 24.1 – 30.5 cm)	
Caster Tires	11" x 4" – 5" Flat-Free Semi-Pneumatic (27.9 x 10.2 – 12.7 cm)															13" x 6.5" – 6" Flat-Free Semi-Pneumatic (33 x 16.5 – 15.2 cm)	
Fuel/Capacity	Gas/10.5-Gal (39.7 L)															Gas/10.5-Gal (39.7 L)	
Digital Hour Meter	Standard															Standard	
Hydraulic Drive System	▶ Unitized Pumps & Wheel Motors															▶ Unitized Pumps & Wheel Motors	
Pump	10cc/rev															13cc/rev	
Wheel Motor	10 cir															13cc/rev	
Maximum Forward Speed	▶ 10 mph (16.1 km/h)															▶ 12 mph (19.3 km/h)	
Throttle Control	Manual															▶ Electronic	
Clutch	Electromagnetic															Electromagnetic	
MOWING DECKS																	
Deck Size	▶ 48" (121.9 cm)		48" (121.9 cm)		▶ 52" (132.1 cm)		52" (132.1 cm)		▶ 60" (152.4 cm)		60" (152.4 cm)		60" (152.4 cm)		52" (132.1 cm)		
Cutting Deck	7-Gauge TURBO FORCE®															7-Gauge TURBO FORCE®	
Bullnose Bumper	Standard															Standard	
Adjustable Discharge Baffle	Standard															Standard	
Rubber Discharge Chute	Standard															Standard	
Deck Lift Design	▶ Extension Spring															▶ Extension Spring	
Spindle Housings	9 3/8" (23.8 cm) Diameter Cast Aluminum															9 3/8" (23.8 cm) Diameter Cast Aluminum	
1" (2.5 cm) Heavy-Duty Spindle Shaft	Standard															Standard	
Spindle Bearings	Maintenance-Free															Maintenance-Free	
Cutting Height	▶ 1.5" – 5.0" (3.8 – 12.7 cm)															▶ 1.5" – 5.0" (3.8 – 12.7 cm)	
Blades	.204" (.5 cm) Heat-Treated Steel															.204" (.5 cm) Heat-Treated Steel	
Blade Tip Speed	18,500+ ft/min															18,500+ ft/min	
Belt Construction	Aramid Fiber V-Belt															Aramid Fiber V-Belt	
Anti-Scalp Rollers	▶ Optional								▶ Standard								Standard
Carrier Frame Construction	3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)															3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)	
FEATURES																	
Steering Controls	Twin Lever															Twin Lever	
Operator Platform	Foldable Operator Platform with Suspension															Foldable Operator Platform with Suspension	
WEIGHTS AND MEASUREMENTS																	
Weight	890 lbs.	403.7 kg	881 lbs.	399.6 kg	898 lbs.	407.3 kg	895 lbs.	406 kg	941 lbs.	426.8 kg	941 lbs.	426.8 kg	941 lbs.	426.8 kg	1061 lbs.	481.3 kg	
Height	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm	50.25"	127.6 cm	
Deck Clearance Width	49.5"	125.7 cm	49.5"	125.7 cm	53.5"	135.9 cm	53.5"	135.9 cm	61.5"	156.2 cm	61.5"	156.2 cm	61.5"	156.2 cm	N/A	N/A	
Deflector Width	63.5"	161.3 cm	63.5"	161.3 cm	67.5"	171.5 cm	67.5"	171.5 cm	75.5"	191.8 cm	75.5"	191.8 cm	75.5"	191.8 cm	53.5"	135.9 cm	
Length (Platform Up)	61"	154.9 cm	61"	154.9 cm	61"	154.9 cm	61"	154.9 cm	65"	165.1 cm	65"	165.1 cm	65"	165.1 cm	71"	180.3 cm	
Length (Platform Down)	75"	190.5 cm	75"	190.5 cm	75"	190.5 cm	75"	190.5 cm	79"	200.7 cm	79"	200.7 cm	79"	200.7 cm	85.5"	217.2 cm	

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995.

As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

▶ = Step Up Feature

	GRANDSTAND®															
	HDX 72510		HDX 72514		HDX 72517		HD+ 72507		HD+ 72512		HDM 74534		HDM 74532		HDM 74535	
POWER SYSTEM			NEW		NEW						79532 CARB		NEW		NEW	
Commercial Engines at 3600 RPM*	31 hp Kawasaki FX921 (999cc)		37 hp Briggs & Stratton® Vanguard® EFI w/Oil Guard (993cc)		37 hp Briggs & Stratton® Vanguard® EFI w/Oil Guard (993cc)		35 hp Kawasaki FX1000 (999 cc)				15 hp Kawasaki® FS (603cc)		18.5 hp Kawasaki FS600V (603 cc)			
Starter	Electric						Electric				Electric		Electric			
Heavy-Duty Canister Air Cleaner	▶ Standard						▶ Standard				N/A		▶ Standard			
Drive Tires	▶ 24" x 12" – 12" Turf (61 x 30.5 – 30.5 cm)						20 in. x 10.5 in. - 8 in. (50.8 cm x 26.7 cm - 20.3 cm)				18" x 8.5" – 8" (45.7 x 21.6 – 20.3 cm)		21 in. x 7 in. - 10 in. (53.3 cm x 17.7 cm - 25.4 cm)			
Caster Tires	13" x 6.5" – 6" Flat-Free Semi-Pneumatic (33 x 16.5 – 15.2 cm)						11" x 4" – 5" Flat-Free Semi-Pneumatic (27.9 x 10.2 – 12.7 cm)				11" x 4" – 5" Flat-Free Semi-Pneumatic (27.9 x 10.2 – 12.7 cm)		9 in. x 4.5 in. - 5 in. Semi-Pneumatic (22.8 cm x 11.4 cm - 12.7 cm)			
Fuel/Capacity	Gas/10.5-Gal (39.7 L)						Gas/10.5-Gal (39.7 L)				Gas/7.8-Gal (29.5 L)		Gas/5-Gal (18.9 L)			
Digital Hour Meter	Standard						Standard				Standard		Standard			
Hydraulic Drive System	▶ Unitized Pumps & Wheel Motors						▶ Unitized Pumps & Wheel Motors				Pumps & Wheel Motors		▶ Unitized Pumps & Wheel Motors			
Pump	13cc/rev						10 cc/rev				10cc/rev		13cc/rev			
Wheel Motor	13cc/rev						10 cc/rev				10 cir		13cc/rev			
Maximum Forward Speed	▶ 12 mph (19.3 km/h)						▶ 12 mph (19.3 km/h)				8 mph (12.9 km/h)		7.5 mph (12.0 km/h)			
Throttle Control	▶ Electronic						▶ Electronic				Manual		▶ Electronic			
Clutch	Electromagnetic						Electromagnetic				Electromagnetic		Electromagnetic			
MOWING DECKS																
Deck Size	60" (152.4 cm)		60" (152.4 cm)		▶ 72" (182.9 cm)		52" (132.1 cm)		60" (152.4 cm)		36" (91.4 cm)		32" (81.2cm)		36" (91.4 cm)	
Cutting Deck	7-Gauge TURBO FORCE®						7-Gauge TURBO FORCE®				7-Gauge TURBO FORCE®		7-Gauge TURBO FORCE®			
Bullnose Bumper	Standard						Standard				Standard		Standard			
Adjustable Discharge Baffle	Standard						Standard				Standard		Standard			
Rubber Discharge Chute	Standard						Standard				Standard		Standard			
Deck Lift Design	▶ Extension Spring						▶ Extension Spring				Compression Spring		▶ Extension Spring			
Spindle Housings	9 3/8" (23.8 cm) Diameter Cast Aluminum						9 in / 22.9 cm Diameter Cast Aluminum				Cast Iron		7/75 in/19.7cm Dia Cast Aluminum			
1" (2.5 cm) Heavy-Duty Spindle Shaft	Standard						Standard				Standard		Standard			
Spindle Bearings	Maintenance-Free						Maintenance-Free				Maintenance-Free		Maintenance-Free			
Cutting Height	▶ 1.5" – 5.0" (3.8 – 12.7 cm)						▶ 1.5" – 5.0" (3.8 – 12.7 cm)				1.0" – 5.0" (2.5 – 12.7 cm)		1.0" - 4.5" (2.54 - 11.4 cm)			
Blades	.204" (.5 cm) Heat-Treated Steel						.204" (.5 cm) Heat-Treated Steel				.25" (.6 cm) Heat-Treated Steel		.204" (.5 cm) Heat-Treated Steel			
Blade Tip Speed	18,500+ ft/min						18,500+ ft/min				18,500+ ft/min		18,500+ ft/min			
Belt Construction	Aramid Fiber V-Belt						Aramid Fiber V-Belt				Aramid Fiber V-Belt		Aramid Fiber V-Belt			
Anti-Scalp Rollers	Standard						Optional		Standard		N/A		Rear Only - Standard			
Carrier Frame Construction	3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)						3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)				3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)		3"x1.5"x10-Gauge (7.6cmx3.8cmx10-Gauge)			
FEATURES																
Steering Controls	Twin Lever						Twin Lever				Twin Lever		Twin Lever			
Operator Platform	Foldable Operator Platform with Suspension						Foldable Operator Platform with Suspension				Foldable Operator Platform with Suspension		Foldable Operator Platform with Suspension			
WEIGHTS AND MEASUREMENT																
Weight	1091 lbs.	494.9 kg	1100 lbs.	499.0 kg	1193 lbs.	541.1 kg	949 lb	430 kg	1004 lb	455 kg	833 lbs.	377.8 kg	702 lbs	318.4 kg	779 lbs	353.3 kg
Height	50.25"	127.6 cm	50.25"	127.6 cm	50.25"	127.6 cm	48"	122 cm	48"	122 cm	48"	121.9 cm	47.3"	120.1 cm	47.3"	120.1 cm
Deck Clearance Width	N/A	N/A	N/A	N/A	N/A	N/A	54"	137 cm	62"	158 cm	37.6"	95.5 cm	N/A	N/A	N/A	N/A
Deflector Width	61.5"	156.2 cm	61.5"	156.2 cm	73.75"	187.3 cm	68"	172 cm	76"	193 cm	51.6"	131.1 cm	44.9"	114 cm	48.0"	122 cm
Length (Platform Up)	73.5"	186.7 cm	61.5"	156.2 cm	73.75"	187.3 cm	61"	145 cm	65"	164 cm	61"	154.9 cm	58.1"	147.5 cm	58.1"	147.5 cm
Length (Platform Down)	88.0"	223.5 cm	75.25"	190.5 cm	87.75"	222.9 cm	75"	191 cm	79"	201 cm	74"	188 cm	N/A	N/A	N/A	N/A

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

► = Step Up Feature

TURFMASTER® HDX

30" HEAVY-DUTY MOWERS

60V^{MAX} BATTERY



A few extra inches of deck can save a lot of mowing time—which is exactly why we built the TurfMaster. This machine covers more ground in less time than smaller models, yet it's also easy to handle. Every component from top to bottom is made for heavy use in rough conditions, from curbs to trailers to multiple operators. It offers professional-grade toughness, professional-quality cut, and a major boost for your productivity.

FINISH THE JOB FASTER

With the highly productive 30" deck.

SIMPLIFY OPERATION

With a conventional walk-behind design that's easier to use and control compared to other mower styles.

GET COMMERCIAL-GRADE POWER

For heavy use with the Kawasaki® or Kohler® engines with spin-on oil filter and dual element air filter.

EXTEND MOWING TIME

Between refueling with the large one-gallon gas tank.

GAIN EXCELLENT CONTROL

With the easy-to-operate, two-bail control system.

DISENGAGE BLADES

Without shutting down the engine, thanks to the Blade Brake Clutch (BBC) system.

POWER THROUGH

The toughest jobs with a battery-powered mower made for contractors. The same proven Turfmaster platform meets the quiet, commercial-grade battery power of Toro's Revolution series.

CASTER WHEEL FRONT END SET UP Locking capability to aid with holding straight lines. (Model 22236 Only)



COMMERCIAL-GRADE WHEELS

Rubber tires with co-polymer wheels feature precision ball bearings for long life with less downtime and lower replacement costs.



BLADE BRAKE CLUTCH (BBC)

Allows the operator to disengage the blades without shutting down the engine. Saves time restarting when you have to step away momentarily to move obstacles or empty the bag.



2-POINT HEIGHT OF CUT

Heavy-duty 2-point height of cut (HOC) system makes it easy to adjust deck height. No need to walk around the mower to adjust four different levers.



HEAVY-DUTY COMPONENTS

Every component is designed for the jobs you need to perform, including the durable cast-aluminum frame, the heavy-duty steel deck, and the bullnose front bumper.

	TURFMASTER® HDX				
	22215†	22225† <i>LIMITED QUANTITY</i>	22235†	22232†	22236†
POWER SYSTEM	NEW				
Commercial Engines at 3600 RPM*	Kawasaki® FJ180V KAI	Kohler Command Pro 200 cc	Kohler CV224 Command Pro 224cc	► 60V MAX® 3 - 10 Ah Batteries with Rapid Charger Variable Speed RWD Brushless DC Motor Runtime up to 80 min† Charge Time up to 112 min†	Kohler CV224 Command Pro 224cc
Starter	Recoil			Electric	Recoil
Tires	Front: 9" x 2" (22.8 cm x 5.0 cm) Rubber Tire w/ Co-Polymer Wheels Rear: 10.5" x 3" (26.6 cm x 7.6 cm) Rubber Tire w/ Co-Polymer Wheels			Front: 9" x 2.5" (22.8 cm x 6.35 cm) Rubber Tire w/ Co-Polymer Wheels Rear: 10.5" x 3" (26.6 cm x 7.6 cm) Rubber Tire w/ Co-Polymer Wheels	Front: 9" x 2" (22.8 cm x 5.0 cm) Rubber Tire w/ Co-Polymer Wheels Rear: 10.5" x 3" (26.6 cm x 7.6 cm) Rubber Tire w/ Co-Polymer Wheels
Fuel/Capacity	Gas/1 Gal (3.8 L)			Cut over an acre on a single charge†	Gas/1 Gal (3.8 L)
Transmission	Heavy Duty Self-Propelled				Heavy Duty Self-Propelled
Control System	Two Bail Control System				Two Bail Control System
Maximum Forward Speed	4.0 mph (6.4 km/h)			4.2 mph (6.7 km/h)	4.0 mph (6.4 km/h)
MOWING DECK					
Deck Size	30" (76.2 cm)				
Deck Type	Mulch/Rear Bag/Side Discharge				
Deck Construction	13-Gauge Steel Deck / Cast Aluminum Frame				
Spindle Assemblies	Die Cast Spindle, 17 mm Cold Formed Spindle Shafts				
Cutting Height	1.5" – 5.0" in 1/2" increments (3.8 – 12.7 cm in .6 cm increments)				
Blades	(2) .135" (.3 cm) Thick Steel				
Blade Engagement	Blade Brake Clutch (BBC)			-	Blade Brake Clutch (BBC)
Blade Tip Speed	18,000+ ft/min				
WEIGHTS AND MEASUREMENTS					
Weight	173 lbs. (78.4 kg) Dry Mulch Mode	173 lbs. (78.4 kg) Dry Mulch Mode	187 lbs. (84.8 kg) Dry Mulch Mode	197 lbs. (89.4 kg)	195 lbs. (88.4 kg)
Height**	41" (104.1 cm)	41" (104.1 cm)	41" (104.1 cm)	41" (105.6 cm)	41" (105.6 cm)
Width	32" (81.3 cm)	32" (81.3 cm)	32" (81.3 cm)	31" (81 cm)	32" (81.3 cm)
Length**	66" (167.6 cm)	66" (167.6 cm)	66" (167.6 cm)	65" (167.1 cm)	65" (167.1 cm)

†Battery manufacturer rating = 60V maximum & 54V typical usage. Actual voltage varies with load.

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995.

As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

** Height-of-Cut in position 3, handle assembled and in the highest position.

†CARB compliant model.

1.1 MAXIMUM ACRES PER HOUR

Maximum acres per hour based on 90% efficiency (MPH x width of cut). Actual productivity dependent upon conditions.



IMPACT PROTECTION

Steel bullnose front bumper, brush guard and engine guard protect components from damage.



NEW! CASTER WHEELS

Locking capability to aid with holding straight lines. (Model 22236 Only)

21" COMMERCIAL

HEAVY-DUTY MOWERS



**BUILT ON
PROVEN
PERFORMANCE.**

The 21" Commercial Heavy-Duty lineup delivers the performance and features Toro is known for. In order to stand up to the toughest conditions this lineup is engineered with rugged, commercial-grade components and the Recycler® Cutting System—along with a large, easy-empty bag—ensures consistent, optimal performance. Combine that with premium engines and maintenance-free transmissions and these machines make it easy to get more done every day.

GET AN OUTSTANDING QUALITY OF CUT

With the Recycler® Cutting System—optimized for exceptional mulching and bagging performance.

DESIGNED FOR DURABILITY

From the corrosion-resistant aluminum alloy deck, replaceable steel deck wear plates and tubular engine guard.

REDUCE DOWNTIME

With a 1-gallon fuel tank for longer uninterrupted mowing time.

INCREASE PRODUCTIVITY

With the Blade Brake Clutch (BBC) system, which allows the operator to disengage blades without shutting down the engine.

A BATTERY-POWERED MOWER MADE FOR CONTRACTORS

The new 60V* 21" Heavy-Duty battery-powered mower is engineered for contractor-grade performance with zero engine exhaust emissions. Quiet, durable and easy to use, it gives professionals the quality of cut you need every day.



STEEL DECK WEAR PLATE

Extend the life of your mowing deck with replaceable steel wear plates that protect against bottom and side impacts.*

* Models 22295, 22296, 22297, & 22298



CRANKSHAFT PROTECTOR

The crankshaft protector provides support to prevent damage from blade impact.



FUELED BY BATTERY

The 60V MAX* 21" Heavy Duty mower gives contractor-grade performance, plus it has zero engine exhaust emissions, is quiet, durable and easy to use.



COMMERCIAL-GRADE WHEELS

Tough co-polymer wheels feature precision ball bearings for long life with less downtime and lower replacement costs. These large 9" x 2" wheels also provide a turf-friendly footprint.

21" COMMERCIAL HEAVY-DUTY MOWERS

22282 (HP, ZS) 22284 (HP, ZS) 22287 (SP, ZS) 22295 (SP, ZS) 22296 (SP, BBC) 22297 (SP, ZS)[†] 22298 (SP, BBC)

POWER SYSTEM

Commercial Engines at 3600 RPM*	▶ 60V MAX* 2 - 7.5 Ah Batteries with Rapid Charger Variable Speed RWD Brushless DC Motor Runtime up to 60 min† Charge Time up to 71 min†	▶ 60V MAX* 1 - 10.0 Ah Batteries with Rapid Charger Variable Speed RWD Brushless DC Motor Runtime up to 80 min† Charge Time up to 90 min†	Kohler® CV173 Variable Speed RWD	▶ Honda® GXV160 3-Speed RWD		▶ Kawasaki FJ180V 3-Speed RW	
Starter	Electric			Recoil			
Tires	9" x 2" (22.8 x 5.1 cm) Rubber Tires						
Fuel/Capacity	Cut up to .4 acre in single charge†			Gas/1 Gal (3.8 L)			
Transmission	Self-Propelled Variable-Speed RWD			Self-Propelled 3-Speed RWD			
Control System	Two Bail Control System			Single Bail	Two-Bail Control System	Single Bail	Two-Bail Control System
Maximum Forward Speed	4.2 mph (6.8 km/h)						

MOWING DECK

Deck Size	21" (53.3 cm)					
Deck Type	Recycler [®] Cutting System Rear Bagging					
Deck Construction	Aluminum Alloy					
Cutting Height	1.0" – 4.5" in 1/2" increments (2.5 – 11.2 cm in 1.3 cm increments)					
Blades	0.135" (.3 cm) Steel with Blade Stiffener					
Blade Engagement	Zone Start			▶ Blade Brake Clutch (BBC)	Zone Start	▶ Blade Brake Clutch (BBC)
Blade Tip Speed	15,320+ ft/min			▶ 18,000+ ft/min		

WEIGHTS AND MEASUREMENTS

Weight	99 lbs.	44.9 kg	99 lbs.	44.9 kg	124 lbs.	56.2 kg	117 lbs.	53.1 kg	121 lbs.	54.9 kg	120 lbs.	54.4 kg	124 lbs.	56.2 kg
Height**	40"	101.6 cm	40"	101.6 cm	40"	101.6 cm	40"	101.6 cm	40"	101.6 cm	40"	101.6 cm	40"	101.6 cm
Width	21.5"	54.6 cm	21.5"	54.6 cm	21.5"	54.6 cm	21.5"	54.6 cm	21.5"	54.6 cm	21.5"	54.6 cm	21.5"	54.6 cm
Length**	59"	149.9 cm	59"	149.9 cm	59"	149.9 cm	59"	149.9 cm	59"	149.9 cm	59"	149.9 cm	59"	149.9 cm

HP = Hand-Push ZS = Zone Start SP = Self-Propelled BSS = Blade Stop System BBC = Blade Brake Clutch

[^] Battery manufacturer rating = 60V maximum & 54V typical usage. Actual voltage varies with load. [†]Based on controlled laboratory testing of product. Runtime varies with load.

Charge time may vary based on environmental conditions. Charge time based on temperate conditions using rapid charger.

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995.

As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

** Height-of-Cut in position 3, handle assembled and in the highest position. [†]CARB compliant model.

▶ = Step Up Feature

MAXIMUM OF
0.8 Acres

COVERED PER HOUR

Maximum acres per hour based on 90% efficiency (MPH x width of cut). Actual productivity dependent upon conditions.



RECYCLER[®] CUTTING SYSTEM

Patented Recycler Cutting System directs grass clippings deep into the turf to provide a "just bagged" appearance without the hassle of clipping collection and disposal.



REAR BAGGING SYSTEM

A wide opening and ramped tunnel profile maximize bag fill. The large, easy-empty design makes quick work of clipping disposal.



TURF RENOVATION

SPRAYMASTER



HORIZON360
CONTRACTOR BUSINESS SOFTWARE

COMPATIBLE

Get the job done better, faster and easier with the stand-on SprayMaster. The updated design creates more stability and balance resulting in less turf tear up and the flip up hopper allows for easy maintenance. Maximize ground coverage and reduce fill-up stops with two spray tanks with up to 60-gallon capacity, 250-pound hopper and 5-gallon fuel tank.

MAXIMUM OF
4.0 Acres
COVERED PER HOUR



FILL UP HOPPER

Maintenance is a breeze with the flip up hopper that provides easy access to the engine.



LARGE CAPACITY

Maximize ground coverage and reduce fill-up stops with two spray tanks that hold up to 60 gallons, 250-pound hopper capacity, and a 5-gallon fuel tank.



RIDE IN STYLE

The new design allows for increase balance and stability and features larger wheels, improved hopper cover, and custom-stitched knee pad.

	LEAN-TO-STEER SPREADER/SPRAYER	SPRAYMASTER 24 GALLON STAND-ON	SPRAYMASTER 40 GALLON STAND-ON	SPRAYMASTER 60 GALLON STAND-ON	SPRAYMASTER 60 GALLON STAND-ON
	34230	34246	34242	34240	34243
POWER AND DRIVE SYSTEM					
Engine*	Kohler® 9.5 hp	16 hp Twin Vanguard	▶ 21 hp Twin Vanguard		▶ 23 hp Twin Vanguard
Engine Orientation	Horizontal				
Fuel Capacity	Gas/1.85 Gal (7 L)	5 Gal (18.9 L) w/fuel gauge			
Electric Start	Yes	Yes	Yes	Yes	Yes
Transmission	Hydrostatic				
Maximum Forward Speed	5.5 mph (8.6 km/h)	7 mph (11.3 km/h)	▶ 10 mph (16.1 mph)	10 mph (16.1 mph)	10 mph (16.1 mph)
SPREADER SYSTEM					
Hopper Size	175 lbs (79.4 kg)	150 lbs (68.0 kg)	▶ 250 lbs (113.4 kg)	250 lbs (113.4 kg)	250 lbs (113.4 kg)
Fertilizer Capacity	225 lbs (102.1 kg)	2 Rear Boxes - 50 lbs (22.7 kg) each			
Spread Width	Adjustable from 4'-22" (1.2 - 6.7 m)	Adjustable up to 25' (0.9 - 7.6 m)			
Deflector Shield	Molded Plastic	Molded Plastic	Molded Plastic	Molded Plastic	Molded Plastic
Spinner Motor	Electric	Electric	Electric	Electric	Electric
SPRAY SYSTEM					
Pump Capacity	5 GPM	5.3 GPM			
Spray Capacity	20 Gal	24 Gal (2 - 12 Gal)	▶ 40 Gal (2 - 20 Gal)	▶ 60 Gal (2 - 30 Gal)	
Spray Width	4 or 10 ft (1.2 or 3.0 m)	2, 4, 6 or 8 ft (0.6, 1.2, 1.8 or 2.4 m)		▶ 2, 4, 6, 8 or 10 ft (0.6, 1.2, 1.8, 2.4 or 3.0 m)	
Boom	N/A	3-Section, Bi-Directional Breakaway Wings			
Spot Spray Hose	15 ft (4.6 m) Coil Hose	15 ft (4.6 m) Coil Hose	▶ 75 ft (22.9 m) Hose Reel		▶ 75 ft (22.9 m) Hose Reel
WEIGHTS AND MEASUREMENTS					
Weight	500 lbs. (226.8 kg)	698 lbs. (316.7 kg)	896 lbs. (406.4 kg)	912 lbs. (413.7 kg)	912 lbs. (413.7 kg)
Height	51.5" (130.8 cm)	48" (121.9 cm)	50" (127.0 cm)	50" (127.0 cm)	50" (127.0 cm)
Width	35.5" (90.2 cm)	36" (91.4 cm)	46" (116.8 cm)	52" (132.1 cm)	52" (132.1 cm)
Length	67.5" (171.5 cm)	70.5" (179.1 cm)	73" (185.4 cm)	72" (182.9 cm)	72" (182.9 cm)

*The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

TURF RENOVATION

24" & 30" STAND-ON AERATOR



HEALTHY TURF STARTS HERE.



HORIZON360
CONTRACTOR BUSINESS SOFTWARE

COMPATIBLE

Get twice the productivity of a 21" walk-behind aerator with the new 24" stand-on model. Built for the demands of busy landscape contractors, it packs the power of a larger model in a smaller footprint so you can maneuver with ease. Now you can reach areas that could previously only be accessed by a walk-behind unit, saving time on projects both large and small.

MANEUVER IN TIGHT SPACES

With a compact design that fits through a standard 36" gate.

NAVIGATE WITH EASE

With intuitive controls that function a lot like a mower, saving time.

GET A SMOOTH RIDE

With the floating operator platform that isolates vibrations.

KEEP CONTROL EASY

With a foot pedal to raise and lower tines.

VARY PLUG LENGTH ON THE FLY

By finely tuning the hydraulic system. It applies up to 1,200 lbs of down pressure on the tines to pull up to 5" cores.

	24" Stand-On Aerator (61 cm)		30" Stand-On Aerator (76.2 cm)	
	39514 [†]		39521 [†]	
POWER SYSTEM				
Engine	Kohler® CH 440		▶ Kawasaki® FS541V V-Twin	
Fuel/Capacity	Gas/1.85 Gal (7 L)		▶ Gas/5 Gal (18.9 L)	
Maximum Forward Speed	Up to 6.8 mph (11.3 km/h) fwd, 2.2 mph (3.5 km/h) rev		▶ Up to 7.5 mph (12.1 km/h) fwd, 2.2 (3.5 km/h) mph rev	
CAPACITIES				
Coverage (Per Hour)	1.5 Acres		▶ 2.0 Acres	
Working Width	24" (60.9 cm)		▶ 30" (76.2 cm)	
Tines	36		▶ 48	
Aerating Width	24" (60.9 cm)		▶ 30" (76.2 cm)	
WEIGHT AND MEASUREMENTS				
Weight	856 lbs.	388 kg	1,015 lbs.	460.4 kg
Height	51.02"	129.6 cm	53"	134.6 cm
Width	35.5"	90.2 cm	48"	121.9 cm
Length	68.62"	174.3 cm	65"	165.1 cm

[†]CARB compliant model.

▶ = Step Up Feature



CONSISTENT POWER

Electronic depth control optimizes power and hydraulics, ensuring consistent core depths on any terrain. Hydraforce valve adjusts operator weight.



INTUITIVE CONTROLS

All necessary functions are at the operator's fingertips, including depth control with supervisor maximum-depth lockout, maintenance reminders and tine activation lockout.

TURF RENOVATION



HORIZON360
CONTRACTOR BUSINESS SOFTWARE

COMPATIBLE

HEALTHY TURF CAN MAKE ALL THE DIFFERENCE.

Toro's turf renovation line combines heavy-duty commercial durability with features that save time—including mower-inspired controls and exceptional maneuverability. In addition to that, you'll also get the speed and fuel capacity you need to push your productivity to the max.



BRUSHCUTTER

HANDLE TOUGH BRUSH

Up to 6' tall and saplings up to 2" in diameter with flail blade for increased cutting performance.

MANEUVER EASILY

Over uneven terrain with a pivoting deck and one-hand control feature.

GET TRACTION

On slopes or in ditches or culverts with sealant-filled aggressive-tread tires.

GAIN DURABILITY

From the high-strength steel deck and large-diameter pulleys.



20" HYDRAULIC SLIT SEEDER

MAKE TIGHT TURNS WITH ONE HAND

Thanks to the variable speed drive system, which handles like a self-propelled mower.

MANEUVER ON HILLS

With the stability of a wide base.

MAXIMIZE DURABILITY

With solid 11-gauge steel construction and high-carbon, heat-treated spring steel blades.

ADJUST SEED FLOW RATE

For the application and seed type.



18" MECHANICAL POWER RAKE

MAKE TRANSPORT EASY

With a compact, lightweight design.

SIMPLIFY OPERATION

With centrifugal clutch blade engagements.

CONVERT TO SEEDING

With optional accessories for spring and fall use in one machine.

HANDLE ANY DETHATCHING PROJECT

With 32 flail blades on 1.5" spacing.

	20" (50.8 CM) HYDRAULIC SLIT SEEDER	18" (45.7 CM) MECHANICAL POWER RAKE	BRUSH CUTTER
	33512 [†]	33513 [†]	33521 [†]
SPECIFICATIONS			
Engine	Subaru® EX27	Honda GX160 (Horizontal Shaft)	15.5 hp Briggs and Stratton Professional
Fuel Capacity	1.6 Gal (6.1 L)	.82 Gal (3.1 L)	1 Gal (3.8 L)
Cutting Width	—	—	28" (71.1 cm)
Cutting Height	—	—	3-3/4" (9.5 cm)
Working Width	20" (50.8 cm)	18" (45.7 cm)	—
Depth	Up to 1" (2.5 cm)	1/8" – 1/2" (0.3 - 1.3 cm)	—
Width	30" (76.2 cm)	28" (71.1 cm)	30" (76.2 cm)
Height	28" (71.1 cm) (Handle Folded) 45" (114.3 cm) (Handle Working)	25" (63.5 cm) (Handle Folded) 37" (94 cm) (Handle Working)	42" (106.7 cm)
Length	38" (96.5 cm) (Handle Folded) 54" (137.1 cm) (Handle Working)	34" (86.4 cm) (Handle Folded) 44" (111.8 cm) (Handle Working)	87" (221 cm)
Weight	270 lbs. (122.4 kg)	127 lbs. (57.6 kg)	375 lbs. (170.1 kg)
Ground Speed	Up to 3 mph (4.8 km/h) fwd, 2.2 (3.5 km/h) mph rev	Push Propelled	—
Coverage (Per Hour)	—	—	—
Seed Hopper Capacity	40 lbs. (18.1 kg)	—	—
Tines/Blades/Broom	10 Verticutting Blades	32 Flail Blades, 1.5" (3.8 cm) spacing	—

Core and cutting depth vary depending on ground conditions. [†]CARB compliant model.



COMMERCIAL SNOW BLOWERS

 **#1**
AMERICA'S
SNOW BLOWER BRAND

KICK OLD MAN WINTER'S BUTT

**SHOW DEEP SNOW WHO'S BOSS
WITH A SNOW BLOWER THAT GIVES YOU
PRECISION CONTROL AND COMMERCIAL DURABILITY.**

Choose single-stage, two-stage, tracks, or a commercial broom and make snow blowing less work this winter with America's #1 snow blower brand¹.

¹Based on average TraQline dollar share for snow blower market as of September 2024



HORIZON360
CONTRACTOR BUSINESS SOFTWARE

COMPATIBLE

LARGER 252cc ENGINE AVAILABLE!



POWER CLEAR® COMMERCIAL SINGLE-STAGE POWER TO BLAST THROUGH SNOW.

Adding a Toro single-stage to your fleet can save you time and make you more money. You'll have no problems blasting through snow with the Power Clear 212cc 4-cycle OHV engine. For extra power on bigger jobs, step up to the 252cc model. Either way, you'll enjoy serious snow-crushing power to get the job done fast.

MODEL 38754, 38755, 39922



POWER MAX® HEAVY DUTY TWO-STAGE PERFECT FOR THE TOUGHEST CONDITIONS.

When the snow gets serious, counter mother nature with a Power Max HD snow blower. Out-muscle the competition with commercial-grade features for added durability such as reinforced 1-piece handle, drift cutters, and heavy-duty cast iron skids. Plus all-steel construction and powerful engines to throw distances up to 60+ feet.*

MODELS 38843, 38844



POWER TRX™ HEAVY DUTY TWO-STAGE MONSTER STORM ROARING IN? ROAR BACK.

Winter gets out of your way as you throw snow 60+ feet.* Tracks provide increased stability for use on the toughest slopes and steepest terrain. Hydrostatic transmission allows for self-propelled operation; plus smoother handling, longer life and less maintenance.

MODEL 38890, 38891

* Throw distance will vary with conditions.

	CORE			PREMIUM			CONTRACTOR GRADE					
	POWER CLEAR® 518 ZR	POWER CLEAR® 721 R	POWER CLEAR® 721 QZE	POWER CLEAR® 518 ZE	POWER CLEAR® 721 E	POWER CLEAR® 821 QZE	COMMERCIAL POWER CLEAR® 721 R-C	COMMERCIAL POWER CLEAR® 821 R-C	COMMERCIAL POWER MAX® HD 1428 OHXE	COMMERCIAL POWER MAX® HD 1432 OHXE	COMMERCIAL POWER TRX™ HD 1428 OHXE	COMMERCIAL POWER TRX™ HD 1432 OHXE
MODEL	38474	38752	38756	38475	38753	38757	38754	38755	38843	38844	38890	38891
CLEARING WIDTH	18" / 45.7 cm	21" / 53.3 cm	21" / 53.3 cm	18" / 45.7 cm	21" / 53.3 cm	21" / 53.3 cm	21" / 53.3 cm w/ Extended Life Paddles	21" / 53.3 cm w/ Extended Life Paddles	28" / 71.1 cm	32" / 81.3 cm	28" / 71.1 cm	32" / 81.3 cm
SNOW CUT DEPTH	12" / 30.5 cm	12.5" / 31.2 cm	12.5" / 31.2 cm	12" / 30.5 cm	12.5" / 31.2 cm	12.5" / 31.2 cm	12.5" / 31.2 cm	12.5" / 31.2 cm	21" / 53.3 cm	21" / 53.3 cm	21" / 53.3 cm	21" / 53.3 cm
ENGINE	99cc Toro Premium OHV	212cc Toro Premium OHV	212cc Toro Premium OHV	99cc Toro Premium OHV	212cc Toro Premium OHV	252cc Toro Premium OHV	212cc Toro Premium OHV	212cc Toro Premium OHV	420cc Toro Premium OHV	420cc Toro Premium OHV	420cc Toro Premium OHV	420cc Toro Premium OHV
DRIVE SYSTEM	Rotor Propelled	Self-Propelled Power Propel®	Self-Propelled Power Propel®	Rotor Propelled	Self-Propelled Power Propel®	Self-Propelled Power Propel®	Self-Propelled Power Propel®	Self-Propelled Power Propel®	Power Steering	Power Steering	Self-Propelled Hydrostatic Transmission and Power Steering	Self-Propelled Hydrostatic Transmission and Power Steering
STARTING	Recoil	Recoil	Electric	Electric	Electric	Electric	Recoil	Recoil	Electric	Electric	Electric	Electric
THROWING DISTANCE*	Up to 25' / 7.6 m	Up to 35' / 10.7 m	Up to 35' / 10.7 m	Up to 25' / 7.6 m	Up to 35' / 10.7 m	Up to 40' / 12.2 m	Up to 35' / 10.7 m	Up to 40' / 12.2 m	Up to 60'+ / 18.3 m+	Up to 60'+ / 18.3 m+	Up to 60'+ / 18.3 m+	Up to 60'+ / 18.3 m+
AUGER SYSTEM	Power Curve	Power Curve	Power Curve	Power Curve	Power Curve	Power Curve	Power Curve	Power Curve	Power Max Anti-Clogging	Power Max Anti-Clogging	Power Max Anti-Clogging	Power Max Anti-Clogging
HANDLE	Standard	Ergonomic	Ergonomic	Standard	Ergonomic	Ergonomic	Reinforced & Ergonomic Handle	Reinforced & Ergonomic Handle	Commercial	Commercial	Commercial	Commercial
DEFLECTOR	Locking	Locking	Locking	Locking	Locking	Locking	Locking	Locking	Double	Double	Double	Double
CHUTE CONTROL	Chute Mounted	Chute Mounted	Quick Chute	Chute Mounted	Chute Mounted	Quick Chute	Chute Mounted	Chute Mounted	Quick Stick®	Quick Stick®	Quick Stick®	Quick Stick®
TIRES	6" x 1.5" / 15.2 x 3.8 cm	7" x 1.75" / 17.8 x 4.4 cm	7" x 1.75" / 17.8 x 4.4 cm	6" x 1.5" / 15.2 x 3.8 cm	7" x 1.75" / 17.8 x 4.4 cm	7" x 1.75" / 17.8 x 4.4 cm	7" x 1.75" / 17.8 x 4.4 cm	7" x 1.75" / 17.8 x 4.4 cm	16" / 40.6 cm	16" / 40.6 cm	Tracked	Tracked
WARRANTY**	2-Year Limited 2-Year Guaranteed to Start			2-Year Limited 2-Year Guaranteed to Start			2-Year Limited Residential, 1-Year Limited Commercial 2-Year Guaranteed to Start Residential Only		5-Year Limited / 1-Year Commercial	5-Year Limited / 1-Year Commercial	5-Year Limited / 1-Year Commercial	5-Year Limited / 1-Year Commercial

► = Step Up Feature

**Based on controlled laboratory testing of product. Capacities and throw distance vary with load.

***See retailer for complete warranty details.

60V^{MAX} BATTERY SNOW BLOWERS



EASY TO CONTROL, 60-VOLT MUSCLE THAT NEVER GETS GASSED

If you've never experienced a Flex Force Power System® snow blower before, you're in for a battery powered snow-destroyin' treat. They not only throw snow up to 45 feet†, they can clear up to a 45 parked car driveway† on a single charge. We've got a solution for every driveway no matter how much you have to clear.

60V POWER MAX® E24

- 24" / 61 cm Clearing Width
- Anti-Clogging System
- Quick Stick® Chute Control
- LED Headlight

1 X 10.0 AH
20 CAR CLEARING
CAPABILITY
OUT OF THE BOX

UP TO 60 CAR
CLEARING CAPABILITY
W/OPTIONAL
2 ADDITIONAL 66810
10.0 AH BATTERIES

60V POWER MAX® E26

- 26" / 66 cm Clearing Width
- Anti-Clogging System
- Quick Stick® Chute Control
- LED Headlight
- Hand Warmers

2 X 7.5 AH
30 CAR CLEARING
CAPABILITY
OUT OF THE BOX

7.5 AH
45 CAR CLEARING
CAPABILITY
W/OPTIONAL 88675
THIRD BATTERY

60V MAX* SINGLE-STAGE POWER CLEAR®



SNOWDRIFT STRENGTH

All the power to break through heavy, wet snow and throw it up to 40 feet†.



TWO BATTERY PORTS

Part of the Toro 60V Flex-Force Power System® with 2 battery ports available, so you can keep going and going.



SHREDS SNOW FAST


Power Propel® technology blasts through the toughest drifts and crustiest snow. Use its muscle without taxing yours.

60V MAX* IN-LINE TWO-STAGE SNOWMASTER®



LIGHTNING FAST

Tear through rough snow and ice in record time with the powerful, engineered auger. With a tall auger housing and guaranteed-for-life chute, even the toughest end-of-driveway snow has met its match.



QUICK STICK® CHUTE CONTROL

Change the chute AND deflector direction with a single, smooth motion thanks to the Quick Stick chute control.



PERSONAL PACE® SELF-PROPEL SYSTEM

Self-propel technology that doesn't push or pull you around. It goes when you go, in perfect harmony with your walking pace, plus, rear-wheel drive for better traction in any snow condition.

*Battery manufacturer rating = 60V maximum & 54V typical usage. Actual voltage varies with load. †Based on controlled laboratory testing of product. Capacities and throw distance vary with load. Charge time may vary based on environmental conditions.
**When compared to model 39901. Snow clearing speeds may vary. *See retailer for complete warranty details.

	CORE					PREMIUM		
	60V POWER SHOVEL™	SINGLE-STAGE POWER CLEAR® 60V E21	SNOWMASTER® 60V E24	TWO-STAGE POWER MAX® 60V E24	TWO-STAGE POWER MAX® 60V E24	SP SINGLE-STAGE POWER CLEAR® 60V E21	SNOWMASTER® 60V E24	TWO-STAGE POWER MAX® HD 60V E26
MODEL	39909	39901	39914	39924	39925	39921	39915	39926
CLEARING WIDTH	12" / 30.5 cm	21" / 53.3 cm	24" / 61.0 cm	24" / 61.0 cm	24" / 61.0 cm	21" / 53.3 cm	24" / 61 cm	26" / 66.0 cm
CLEARING CAPACITY**	Decks, patios and up to 4 parked cars	Up to 12 parked cars	Up to 20 parked cars	Up to 24 parked cars (12 cars per battery) Up to 15 cars more with additional 3rd battery	Up to 20 parked cars	Up to 15 parked cars	Up to 30 parked cars	Up to 30 parked cars (15 cars per battery) Up to 15 cars more with additional 3rd battery
SNOW CUT DEPTH	6" / 15.2 cm	12" / 30.5 cm	18" / 45.7 cm	20" / 50.8 cm	20" / 50.8 cm	12" / 30.5 cm	18" / 45.7 cm	20" / 50.8 cm
BATTERY	1 x 2.5 ah	1 x 7.5 ah	1 x 10.0 ah	2 x 6.0 ah	1 x 10.0 ah	1 x 10.0 ah	1 x 10.0 ah + 1 x 5.0 ah	2 x 7.5 ah
CHARGE TIME	60 min	180 min	300 min	150 min	150 min	180 min	300 min	180 min
THROWING DISTANCE**	Up to 25' / 7.6 m	Up to 40' / 12.2 m	Up to 40' / 12.2 m	Up to 45' / 13.7 m	Up to 45' / 13.7 m	Up to 30' / 9.1 m	Up to 40' / 12.2 m	Up to 45' / 13.7 m
AUGER SYSTEM	Power Curve®	Patent Pending Power Edge™	In-Line Two Stage	Power Max Anti-Clogging System	Power Max Anti-Clogging System	Power Curve® Self-Propel	In-Line Two Stage	Power Max Anti-Clogging System
AUGER DIAMETER	6.5" / 16.5 cm	7" / 17.8 cm	10" / 25.4 cm	11" / 27.9 cm	11" / 27.9 cm	8.5" / 21.6 cm	10" / 25.4 cm	11" / 27.9 cm
IMPELLER DIAMETER	-	-	-	11" / 27.9 cm	11" / 27.9 cm	-	-	11" / 27.9 cm
AUGER GEARBOX	-	-	-	Hardened Gears; No Shear Pins	Hardened Gears; No Shear Pins	-	-	Hardened Gears; No Shear Pins
HANDLE	-	Adjustable	Personal Pace®	Standard	Standard	Ergonomic	Personal Pace®	Heavy-Duty
DEFLECTOR	-	Locking	Single	Single	Single	Locking	Single	Single
CHUTE CONTROL	-	Quick Turn	Quick Stick®	Quick Stick®	Quick Stick®	Chute Mounted	Quick Stick®	Quick Stick®
CHUTE CONSTRUCTION	-	Sub Zero Curved Chute	High Capacity Chute	Steel	Steel	High Capacity Chute	High Capacity Chute	Steel
TIRES	-	6 7/8" x 2" 17.5 cm x 5.1 cm	11" / 27.9 cm	15" / 38.1 cm	15" / 38.1 cm	7" / 17.8 cm	11" / 27.9 cm	15" / 38.1 cm
HAND WARMERS	-	-	-	-	-	-	-	Standard
LIGHT	-	Panoramic LED	-	LED	LED	Panoramic LED	Panoramic LED	LED
WARRANTY***	3-Year Limited, 3-Year Battery	2-Year Limited, 3-Year Battery	2-Year Limited, 3-Year Battery	3-Year Limited, 3-Year Battery	3-Year Limited, 3-Year Battery	2-Year Limited, 3-Year Battery	2-Year Limited, 3-Year Battery	3-Year Limited, 3-Year Battery
BARE TOOL MODEL #	39909T	39901T	-	-	-	39921T	39915T	39926T

► = Step Up Feature

60V MAX* TWO-STAGE POWER MAX®



ZERO COMPROMISES

Same rugged, heavy-duty steel construction as Toro gas-powered snow blowers, with LED lights, hardened gears and no shear pins to break.



GO THREE ROUNDS WITH OLD MAN WINTER

Three battery ports, this machine has all the power you need to get the job done right.



POWER UP


All the features you love – Quick Stick® chute control, rugged 15" / 38 cm tires, anti-clogging system, and more.

FIND THE KIND OF SUPPORT YOU CAN COUNT ON.



REAL PEOPLE. REAL SUPPORT.

Count on our national network of factory-authorized dealers for genuine Toro parts and service support. They receive ongoing training and maintain a substantial inventory with an impressive 98% fill rate on parts.



CUSTOMER CARE

888-384-5153 (US) / 800-544-5364 (Canada)

They're available Monday through Friday between 8:00 and 4:30 CST to answer your questions about equipment, parts, service and more.




ACCESS AT YOUR FINGERTIPS

Find a dealer, look up parts and check out special offers at toro.com/LCE — designed for smartphones. Visit toro.com (in the US) or toro.ca (in Canada) for owner's manuals, interactive manuals, safety information, product registration and answers to frequently asked questions.



SAFETY EDUCATION

We offer many tools to help train and protect you and your crew, including online interactive training, multi-lingual manuals and safety quizzes. See the product safety information page on toro.com for details.



PERFORMANCE EVALUATIONS

Each new Toro product is subjected to extensive testing, as well as coast-to-coast field evaluations in various turf and environmental conditions. Landscape professionals also test equipment in the field to ensure it performs as intended.

E-Z VAC BAGGERS



E-Z VAC TWIN BAGGER

Deck-mounted, spindle-driven fan; 2 commercial-grade mesh bags with reinforced front and bottom.

10 cu. ft. capacity (8 bushels).

E-Z VAC TRIPLE BAGGER

Deck-mounted, spindle-driven fan; 3 commercial-grade mesh bags with reinforced front and bottom.

16.7 cu. ft. capacity (13.4 bushels).

E-Z VAC DFS (DUMP-FROM-THE-SEAT)

Deck-mounted, spindle-driven fan; Dump-From-the-Seat, commercial-grade steel and polyethylene hopper.

48"/52" capacity: 8.3 cu. ft. (6.7 bushels)

60"/72" capacity: 13.7 cu. ft. capacity (11 bushels).



Z MASTER® COLLECTION SYSTEMS

2000 SERIES

PART

E-Z Vac Twin Soft Heavy Duty Bagger
10 cu. ft. capacity (8 bushels)

78431

E-Z Vac Twin Soft Standard Bagger
10 cu. ft. capacity (8 bushels)

78481

3000, 5000, 6000 SERIES

E-Z Vac Twin Soft Bagger - 48"/52" Decks
10 cu. ft. capacity (8 bushels)

78562

E-Z Vac Triple Soft Bagger - 60" Decks
16.7 cu. ft. capacity (13.4 bushels)

78563

E-Z Vac Triple Soft Bagger - 72" Decks
16.7 cu. ft. capacity (13.4 bushels)

78555

E-Z Vac DFS Rear Bagger - 48"/52" Decks
8.3 cu. ft. capacity (6.7 bushels)

78566

E-Z Vac DFS Rear Bagger - 60" Decks
13.7 cu. ft. capacity (11 bushels)

78567

E-Z Vac DFS Rear Bagger - 72" Decks
13.7 cu. ft. capacity (11 bushels)

78556

4000 SERIES

E-Z Vac Twin Soft Bagger - 48"/52"/60" Decks
10 cu. ft. capacity (8 bushels)

78463

4000 HDX PRO XL SERIES

E-Z Vac Triple Soft Bagger - 60" Decks
16.7 cu. ft. capacity (13.4 bushels)

78479

E-Z Vac Triple Soft Bagger - 72" Decks
16.7 cu. ft. capacity (13.4 bushels)

78489

E-Z Vac DFS Rear Bagger - 60" Decks
13.7 cu. ft. capacity (11 bushels)

78468

E-Z Vac DFS Rear Bagger - 72" Decks
13.7 cu. ft. capacity (11 bushels)

78474

7500 HDX PRO XL SERIES

E-Z Vac Triple Soft Bagger
16.7 cu. ft. capacity (13.4 bushels)

78560

E-Z Vac Triple Soft Bagger - 72" Decks
16.7 cu. ft. capacity (13.4 bushels)

78489

GRANDSTAND® COLLECTION SYSTEMS

E-Z Vac Twin Soft Heavy Duty Bagger
10 cu. ft. capacity (8 bushels)

78524

*E-Z Vac Bagger and DFS require a blower & deck drive kit with bagger installation.
See retailer or toro.com for correlating drive kit requirements.*

ACCESSORIES


ENHANCE YOUR MOWING EXPERIENCE

GIVE YOUR PRODUCTIVITY AN EXTRA BOOST

with genuine Toro parts and accessories for your Toro GrandStand®, Z Master®, or Mid-size walk-behind.

Some accessories are not available for all models; ask your local dealer for details.

HARD TOP CANOPY & SUN SHADES



Articulating hard top sun canopy or fabric shade for 2-post ROPS shields the operator from the elements. Cool Top ROPS-mounted fan also available to help ease the heat.



PART #	DESCRIPTION
140-4367	Hard Top Articulating Sun Canopy – Z Master 2000 Series (MY2020)
144-3719	Hard Top Articulating Sun Canopy (Sq ROPS) – G3/7500 and MY2021 2000/4000 series
115-4510	Fabric Sunshade – All Z-Masters with ROPS

DELUXE SUSPENSION SEAT



Improves operator comfort and reduces operator fatigue when mowing for longer periods.

PART #	DESCRIPTION
147-2384	Deluxe Suspension Seat Kit – Optional Replacement – 2000 Series
144-2632	Deluxe Suspension Seat Kit – Optional Replacement – 4000 Series
147-4984	Deluxe Suspension Seat Kit – Optional Replacement – 5000, 6000 Series

OPERATOR-CONTROLLED DISCHARGE CHUTE



Three settings allow you to put clippings where you want them.

PART #	DESCRIPTION
117-3600	Operator Controlled Discharge Chute Kit with Trash Bag – 48" (121.9 cm)-72" (182.9 cm) G3, 3000, 5000, 6000 Series
78521	Operator Controlled Discharge Chute – 7000 Series 52" (121.9 cm)-60" (152.4 cm)
78522	Operator Controlled Discharge Chute – 7000 Series 72" (182.9 cm)
117-8565	Operator Controlled Discharge Chute Kit with Trash Bag – GrandStand 36" (91.4 cm) and 40" (101.6 cm)
133-1434	Operator Controlled Discharge Chute Kit with Trash Bag – GrandStand (2016 and newer) 48" (121.9 cm)-60" (152.4 cm)

Z STAND KIT



Exclusive on-board tool quickly elevates the front end of the machine for access to the underside of the deck.

PART #	DESCRIPTION
105-1622	Z Stand Kit – Z200, Z500, 7000 Series
117-0354	Z Stand Kit – 72" (182.9 cm) 5000/6000 Series (Excludes Rear Discharge 74944)
121-4811	Z Stand Kit – 48" (121.9 cm)-60" (152.4 cm) 3000/5000/6000 Series



STRIPING KIT

Creates vivid stripes for a premium "ball park" after-cut appearance.

PART #	DESCRIPTION
107-1630	Striping Kit – Z5000 and 7000 Series TURBO FORCE® Decks – Rubber 52", 60", 72"
108-2162	Striping Kit – 7000 Series TURBO FORCE Decks – Roller
115-7470	Striping Kit – 48" (121.9 cm)-60" (152.4 cm) G3, 3000/5000/6000 Series
115-7480	Striping Kit – 72" (182.9 cm) G3, 3000/5000/6000 Series
117-8560	Striping Kit – 36" (91.4 cm) and 40" (101.6 cm) GrandStand® Mower with 36 in and 42" TURBO FORCE Cutting Unit
133-1436	Striping Kit – 48" (121.9 cm), 52" (132.1 cm) & 60" (152.4 cm) GrandStand Mower with 48", 52" and 60" TURBO FORCE Cutting Unit (2016 models and newer)



MICHELIN® TWEELS®

Highly-durable, non-pneumatic alternative to conventional rear tires. No air pressure to maintain, no more unseated beads, and no more flat tires. No maintenance!

PART #	DESCRIPTION
139-7890	18" Tweel, -.50" Offset – GrandStand 48", 52" and 60" Models
139-7891	24" x12N12 Tweel Turf, -.75" Offset – Z Master 3000/5000/6000 Series, Z Master 60" and 72" Models
139-3649	24" x12N12 Tweel Turf, -2.20" Offset – Titan Max models and Z Master 2000 Series Models
147-4600	26" x 12N12 Tweel Turf, -2.20 Offset – Z Master 4000 Series
147-6337	Caster Tweel - 15x6.5N6: 4000 Series (Must be paired w/ 26" Rear)
147-6294	Caster Tweel - 13x6.5N6: 2000/4000 Series
147-6295	Caster Tweel - 13x6.5N6: 5000/6000/7000 Series



JACK MOUNT KIT

Exclusive on-board tool quickly elevates the front end of the machine for access to the underside of the deck.

PART #	DESCRIPTION
127-6666	Jack Kit – All Z Master 3000/5000/6000 Series
144-2676	Jack Mount Kit – All Z Master 2000/4000/Revolution
144-1993	Jack Mount Kit – Titan and Z Master 2000 Series
146-0696	Jack Mount Kit – Z Master G3/3000/5000/6000 Series



FLAT-FREE TIRES

Semi-pneumatic "flat-free" caster tires help avoid the drain on productivity that results from flat tires. Engineered to deliver the durability of solid tires with the soft, cushioned ride of air-filled tires.

PART #	DESCRIPTION
140-4896	13" – 2000/4000 Series (Black)
145-1919	15" – 4000 Series (Black)
127-9528	13" – 5000/6000 Series (Gray)
126-9344	15" – 7500 Series Traction Unit (Gray)
130-4558	11" – 7500 Series Wing Deck Caster (Gray)
130-2865	13" – 8000 Series (Gray)



SEAT COVER

Makes old seats look new and protects new seats. Cushioned cover is water-resistant and has an elastic cord for a custom fit.

PART #	DESCRIPTION
117-0095	18" (45.7 cm) Seat Cover with Armrest

OUR BEST-SELLING ACCESSORY

RECYCLER® MULCH KITS

Recycler mulching kits deliver the industry's finest mulching performance and reduce mowing time vs. bagging.*

FASTER

Up to 38% faster than bagging*

EASIER

Neat and clean results without the effort of clipping disposal

HEALTHIER

Recycler blades cut and re-cut clippings, then return valuable moisture and nutrients to the turf

CATEGORY	32" (81.3 cm)	36" (91.4 cm)	40" (101.6 cm)	48" (121.9 cm)	52" (132.1 cm)	54" (137.2 cm)	60" (152.4 cm)	72" (182.9 cm)
Mid-Size TURBO FORCE® Deck – Fixed & Floating	110-4915	110-2080	110-2070	110-2060	110-2040			
GrandStand		110-2080	110-2070	139-6650*	139-6653*		139-6655*	139-6659*
Z Master 2000 Series				139-6650*	139-6653*		139-6655*	
Z Master G3, Commercial 3000 Series, Professional 5000 & 6000 Series				139-6650*	139-6653*		139-6655*	139-6659*
Z Master Z400 Series, Z500 Series, Professional 7000 Series				139-6650*	139-6653 or 140-8016*		139-6653 or 140-8017*	140-8018*
PROLINE™ Mid-size		140-1913		140-1914		140-1915	140-1916	



LIGHT KIT

Lights easily mount to the mower frame, and wiring quickly connects to the existing accessory circuit.

PART #	DESCRIPTION
107-9880	Light Kit – 7000 Series and Z100-Z500
116-1154	Light Kit – G3 and 3000/5000/6000 Series
130-8469	Light Kit – 8000 Series Direct Collect Z
133-1437	Light Kit – All GrandStand (2016 and newer)
139-5595	Light Kit – PROLINE Mid-size
133-1495	Flashing Light Kit – All GrandStand (2016 and newer)
144-0389	Base Light Kit 4000 Series



SULKY OPTIONS

Toro offers the Patented Tru-Trak Sulky for Mid-Size mowers and the 2-wheel sulky for the 36"-60" PROLINE models.

PART #	DESCRIPTION
44401	2-Wheel Sulky – PROLINE 36"- 60" (36" models 44409, 44410 & 44436 require Weight Kit Part 138-6866)
30109	Tru-Trak Sulky – Mid-Size Fixed Deck Models



TRAILER HITCH

Improves versatility and allows for simple tow-behind applications.

PART #	DESCRIPTION
109-9487	Hitch Kit – G3 and 3000/5000/6000 Series
99-8925	Hitch Kit – 7000, Z200 and Z500 Series
58924	Magnetic Hitch Pin



TRASH BAG WITH CUP HOLDER

Multiple styles available to hold a drink and other personal items. Bag can be used to collect debris.

PART #	DESCRIPTION
TC26	Trash Bag with Cup Holder – All Z Master (Except 8000 Series)
133-1435	Trash Bag with Cup Holder – GrandStand (2016 models)



TORO 5-GALLON BUCKET

Easily attaches to your TITAN HD, Z Master 2000 Series, or GrandStand to collect debris or carry other items, eliminating extra trips to save you time.

PART #	DESCRIPTION
133-2533	Toro 5-Gallon (18.9 L) Bucket



GAS CANS

Uncomplicated and simple to use, Toro's No-Spill® gas cans take the hassle out of fuel storage.

PART #	DESCRIPTION
127-3200	No Spill (1.25 gal.) (4.7 L)
127-3201	No Spill (2.5 gal.) (9.4 L)
127-3202	No Spill (5 gal.) (18.9 L)
127-3203	Kerosene (5 gal.) (18.9 L)
127-3204	Diesel (5 gal.) (18.9 L)
127-3205	Nozzle Replacement
127-3206	6" (15.2 cm) Flexible Spout Extension

* See Master Parts Viewer for specific model applications on Toro.com or Toro.ca

^Blades not included. Order blades for cast aluminum spindles (MY20 and newer) or cast iron spindles (MY19 and older) separately.

* Respondents in a Texas A&M University study cut their lawns 38% faster when they didn't bag.



SAFETY GLASSES

Part 58928	Matte Black Frame, Clear Anti-Fog Lens
Part 58929	Crystal Black Frame, Clear Anti-Fog Lens
Part 58930	Woodland Camouflage Frame, Clear Anti-Fog Lens
Part 58932	Woodland Camouflage Frame, Green Mirror Anti-Fog Lens
Part 58933	Crystal Brown Frame, Brown Lens
Part 58934	Camouflage Frame, Brown Anti-Fog Lens



INSULATED RIDER CUP

Part 58900	20 oz.
Part 58940	30 oz.



CLASS II SAFETY VEST

Part 58902	Small/Medium
Part 58903	Large/X-Large
Part 58904	XX-Large/XXX-Large

MAINTENANCE PRODUCTS

ENHANCE YOUR MOWING EXPERIENCE



GENUINE TORO® PARTS

To best protect your investment and maintain optimal performance of your turf equipment, count on Toro genuine parts. When it comes to reliability, Toro delivers replacement parts designed to the exact specifications of our equipment. For peace of mind, insist on Toro genuine parts.

PRO PARTS EXPRESS

Ask your dealer about Toro's Parts Pro Express program that saves time and money by shipping parts directly to you, especially those special order items that are needed right away.

TORO LUBRICANTS

Toro Premium Lubricants are specifically engineered for use in Toro outdoor power equipment. Toro's engine oils are formulated, tested and approved by Toro engineers to provide optimal protection and engine life.



OILS & MAINTENANCE KITS

PART #	DESCRIPTION
38280	10W30 4-Cycle Engine Oil (32 oz.) (946.3 mL)
38903	4-Cycle SAE SAE 30 Oil (32 oz.) (946.3 mL)
38916	4-Cycle SAE SAE 30 Oil (18 oz.) (532.3 mL)
114-4713	Hypr Oil High-Performance Hydro Oil (1 qt.) (9 L)
114-4714	Hypr Oil High-Performance Hydro Oil (1 gal.) (3.7 L)
114-4715	Hypr Oil High-Performance Hydro Oil (5 gal.) (18.9 L)
108-1183	Hypr Oil High-Performance Hydro Oil (55 gal.) (208 L)
121-3783	Titan Hydraulic Filter and Service Kit
138-6053	Toro Full Synthetic Oil (32 oz. bottle) (946.3 mL)
139-0627	20W50 Full Synthetic Oil (CK4) (32 oz.) (946.3 mL)
147-6275	Synthetic Electric Motor Drive Oil (Grandstand and Z Master Revolution Product)



PREMIUM FUEL TREATMENT

The ultimate in fuel stability, fuel system cleaning and corrosion prevention. Also keeps fuel fresh for up to two years and guards against rust and oxidation that ethanol can accelerate.

PART #	DESCRIPTION
131-6572	Premium Fuel Treatment (12 oz. bottle) (354.8 mL)



TORO TIRE SEALANT

Say "good-bye" to flat tires forever! Toro Tire Sealant seals most bead and rim leaks and seals punctures up to 1/4" (larger in heavy ply tires). It also prolongs tire life and lasts for the life of the tire. Toro Tire Sealant will not rust or corrode rims. Works in tubeless or tube tires, does not have a shelf-life, and is very competitively priced!

PART #	DESCRIPTION
110-8832	Sealant (32 oz.) (9 L)
110-8833	Sealant (1 gal.) (3.7 L)
110-8834	Sealant (5 gal.) (18.9 L)
110-8835	Sealant Pump (1 gal.) (3.7 L)
110-8836	Sealant Pump (5 gal.) (18.9 L)



TORO ENGINE MAINTENANCE KITS

Includes the engine oil, fuel treatment, air filter, oil filter, fuel filter and spark plug(s) recommended for regular maintenance.

PART #	DESCRIPTION
20295	Toro V-Twin Engine, Heavy-Duty Canister Air Cleaner (Titan HD / Z Master 2000 Series)

Z MASTER® (MyRIDE® SUSPENSION SYSTEM)

PART #	DESCRIPTION
132-5068	Shock Cover
133-1810	Floormat

Z MASTER®

PART #	DESCRIPTION
144-0380	Baffle Kit – 72" (182.9 cm) 5000 Series Rear Discharge (74029)
126-0854	White Deck Bumper Skid – 5000 Series Rear Discharge
127-6650	Anti-Scalp and Wear Bar Kit
132-5986	Electric Deck Lift Kit – 3000/5000/6000 Series (Non MyRIDE®)
161-3550	Electric Deck Lift Kit – 4000 Series
144-2665	Trimmer Mount Kit – 4000 Series
137-9769	Trimmer Mount Kit
137-9216	Bucket Holder Kit

8000 SERIES DIRECT COLLECT Z

PART #	DESCRIPTION
130-8471	Suspension Seat Kit
130-8457	Grass Tub Kit
130-8460	Mulch Kit – 42" (106.7 cm)
130-8463	Mulch Kit – 48" (121.9 cm)
130-8459	Roll Over Protection System (ROPS) Kit
130-8455	Dual Split Caster Kit
130-8470	Automatic Bagging Door Opener Kit
130-8458	Power Hopper Dump Kit
126-7011	Front Bucket Bracket Kit

Z MASTER® 2000

PART #	DESCRIPTION
145-3691	Triple Threat Kit (includes bucket holder, universal mount, and trimmer mount) (2017 MY)
145-3688	Universal Mount Kit (2017 MY)
145-3687	Bucket Holder & Trash Picker Mount Kit (2017 MY)
145-3689	Trimmer Mount Kit
133-2533	Toro 5 Gallon (18.9 L) Bucket
136-1683	ROPS Pin Kit

GRANDSTAND® MULTI FORCE®

PART #	DESCRIPTION
133-5386	Wheel Weight Kit
STB13803	Replacement cutting edge Boss Plow (use with HDW13807 - Hardware Kit)
136-0513	Quick Attach Kit
136-5681	Bucket Mount Kit
133-2533	Toro 5 Gallon (18.9 L) Bucket
137-3952	Bristle Refill Kit
133-1438	GrandStand Accessory Port
137-3920	Rubber Flap Kit - Broom

GRANDSTAND®

PART #	DESCRIPTION
107-1634	Bagger Enhancement Kit – 52" (132.1 cm) and 60" (152.4 cm)
108-4091	Bagger Enhancement Kit – 48" (121.9 cm)
110-2025	Bagger Enhancement Kit – 40" (101.6 cm)
110-2026	Bagger Enhancement Kit – 36" (91.4 cm)
30104	Soft Bagger Kit – 40" (101.6 cm), 48" (121.9 cm), 52" (132.1 cm), 60" (152.4 cm)
121-7515	Soft Bagger Adapter Kit – 36" (91.4 cm)
133-1428	Weight Kit – 48" (121.9 cm), 52" (132.1 cm), 60" (152.4 cm) (2016 models)
133-1438	Electric Accessory Port – 48" (121.9 cm), 52" (132.1 cm), 60" (152.4 cm) (2016 and newer)
133-1439	Height of Cut Block Kit – 48" (121.9 cm), 52" (132.1 cm), 60" (152.4 cm) (2016 and newer)
133-1440	Anti-Scalp Kit – 48" (121.9 cm), 52" (132.1 cm), 60" (152.4 cm) (2016 and newer)
133-1438	GrandStand Accessory Port
133-1441	Trimmer Rack – 48" (121.9 cm), 52", 60" (2016 and newer)

PROLINE MID-SIZE

PART #	DESCRIPTION
139-7860	Soft Bag Kit – Deck Mount
138-6866	Weight Kit
139-5595	Light Kit
139-4063	Height of Cut Blocks
140-4300	Rubber Deflector Kit

MID-SIZE

PART #	DESCRIPTION
30198	Soft Bag Kit – 32" (81.3 cm) 36" (91.4 cm) 48" (121.9 cm) (Non-TURBO FORCE® fixed deck only)
30104	Soft Bag Kit – 36" (91.4 cm) and larger (TURBO FORCE fixed and floating decks)
110-2085	Fixed Deck Weight Kit
115-4190	Chute Gate Kit
110-5024	Wheel and Tire Assembly 9" (22.8 cm) x 3.5" (8.8 cm) – 4" (10.1 cm) (Mid-Sized Fixed/Floating Mowers)

TURFMASTER®

PART #	DESCRIPTION
490-7461	Walk Power Mower Cover – 30" (76.2 cm)
121-5775	Grass Bag Assembly

21" COMMERCIAL

PART #	DESCRIPTION
125-1030	Grass Bag (2014 models and newer)
121-1399-03	Grass Bag Frame Assembly (2014 models and newer)
490-7462	Walk Power Mower Cover (Fits mowers up to 22" (55.8cm)
130-9734	Rear Discharge Kit (2014 models and prior)

SPRAYMASTER

PART #	DESCRIPTION
146-0602	7-Gallon Iso Tank Kit
146-0603	7-Gallon Aux Tank Kit
146-0600	30-Gallon Aux Tank
142-7879	Pump Kit - 7 Gallon
142-7070	Foam Marker Kit - 2 Gallon
142-7876	Light Kit

COMMERCIAL POWER BROOM

PART #	DESCRIPTION
116-8227	Cab Kit
135-2311	Turf Caster Kit
116-8229	Dirt Deflector Kit
116-8230	Debris Box Kit
116-8232	Black Snow/Ice Wafers
116-8233	Yellow Turf Wafers
116-8234	Light Kit
126-0023	Electrical Power Kit
137-3952	Bristle Refill Kit

TURF RENOVATION

PART #	DESCRIPTION
126-2143	Coring Tine Replacements



Count on it.



WHEN WE SAY **COUNT ON IT**, WE MEAN IT

Every product that carries the Toro brand is backed by over 100 years of history, innovation and timeless dependability. We never stop investing in research and development to give our customers the latest features. That's why Toro is one of the best-known, most trusted brands in the business — and why your next mower should be a Toro. We also stand behind our products with a nationwide network of knowledgeable dealers for parts and service support. **Real People. Real Support.**



HORIZON360
CONTRACTOR BUSINESS SOFTWARE

It's About Time.

Software Built to Streamline and Optimize Your Business
Learn more: horizon360.toro.com



EXCLUSIVE TORO FINANCING PROGRAM
Financing available for both consumer and commercial customers. Select from low interest, deferred payment, and fixed pay or revolving charge options. See your local dealer for current promotional and program details, or visit toro.com/financing or toro.ca/financing.

FOLLOW US!



facebook.com/toro.yard



twitter.com/thetorocompany



instagram.com/thetorocompany



youtube.com/toro



pinterest.com/thetorocompany



NATIONAL
ASSOCIATION OF
LANDSCAPE
PROFESSIONALS

Proud Partner

toro.com / toro.ca

©2025 The Toro Company. Bloomington, MN 55420 All rights reserved. Printed in the USA.

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, design and standard equipment without notice and without incurring obligation. See your dealer for details on all our warranties.

Dealer imprint area